Tyrone Camarero Specifications



Camerero SS200T3G-13-2075

Key features

- Single socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family
- Up to 512GB ECC DDR3, up to 1866MHz; 8x DIMM sockets
- 2x M2075 GPU cards pre-installed, 1 (x8) PCI-E 3.0 low-profile slot
- · Integrated IPMI 2.0 with KVM and Dedicated LAN
- Intel® i350 Dual-Port GbE Controller
- 3x Hot-swap 3.5" Drive Bays
- 1400W High-efficiency Power Supply Platinum Level (94%+) Digital Switching Control & PMBus 1.2
- 8x Counter rotating fans w/ optimal fan speed control
- Smart server management tools







Processor/Cache

Processor Intel® Xeon® processor E5-2600

Chipset

Intel® C602 Chipset

System Memory

Memory Capacity 8x 240-pin DDR3 DIMM sockets

Supports up to 256 GB DDR3 ECC

Expansion Slots

PCI-Express 2 (x16) PCI-E 3.0 slots (2x NVIDIA Tesla

M2090 Fermi GPU cards integrated) 1(x8) PCI-E 3.0 slot for I.B. Card

Integrated On-Board

SATA Intel ICH10R SATA 3.0Gbps Controller

RAID 0, 1, 5, 10 support

LAN 2 RJ45 Gigabit Ethernet LAN ports 1

RJ45 Dedicated IPMI LAN port

Add-on Options

RAID Card Optional

Optical Drive None

Front Panel:

LED Indicators Power LED HDD activity LED 2x Network

activity LEDs System Overheat LED / Fan fail LED / Universal Information (UID) LED

Switches Power On/Off Button, System Reset

Button

Drive bays

HDD bays 3x 3.5" Hot-swap drive bays

Power Supply

1400W High-efficiency Power Supply 80Plus Platinum Level (94%+) Digital Switching Control & PMBus 1.2

Cooling System

8x counter-rotating fans with optimal fan speed control

Form Factor

Height 1.7" (43mm) Width 17.2" (437mm) Depth 28.2" (716mm)

E:info@tyronesystems.com

For more/current product information, visit www.tyronesystems.com