

Tyrone Camarero Specifications

Tyrone[®]

Camarero SS200T3G-16-2075

Key features

- Single socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family
- Up to 512GB ECC DDR3, up to 1866MHz; 8x DIMM sockets
- 2x M2075 GPU cards pre-installed, 1 (x8) PCI-E 3.0 low-profile slot
- Integrated IPMI 2.0 with KVM and Dedicated LAN
- Intel® i350 Dual-Port GbE Controller
- 6x Hot-swap 2.5" SATA/SAS/SAS2 Drive Bays
- 1400W high efficiency platinum level (94%+)
- 8x Counter rotating fans w/ optimal fan speed control
- Smart server management tools



Processor/Cache	
Processor	Single socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family
System Bus	1600MHz
Chipset	
	Intel® C602 Chipset
System Memory	
Memory Capacity	8x 240-pin DDR3 DIMM sockets Up to 512GB DDR3 ECC LRDIMM Up to 256GB DDR3 ECC Registered memory (RDIMM)
Expansion Slots	
PCI-Express	2 (x16) PCI-E 3.0 slots (2x NVIDIA Tesla M2075 Fermi GPU cards integrated) 1 (x8) PCI-E 3.0 slot for I.B. Card
Integrated On-Board	
SATA	SATA3 (6Gbps) and SATA2 (3Gbps) RAID 0, 1, 5, 10 support (Windows) RAID 0, 1, 10 support (Linux)
LAN	SATA - SATA 2.0 3Gbps with RAID 0, 1, 5, 10 SATA 3.0 6Gbps with RAID 0, 1, 5, 10
Add-on Options	
Raid	Optional
Optical Drive	None

Front Panel	
LED	Power LED, Hard drive activity LED, 2x Network activity LEDs System Overheat LED / Fan fail LED / UID LED
Switches	Power On/Off button System
Drive Bays	
HDD bays	6x 2.5" Hot-swap drive bay
Peripheral Bays	Optional
Power Supply	
	1400W high efficiency platinum level (94%+)
Cooling System	
	8x counter-rotating fans with optimal fan speed control
Form Factor	
1U Rackmount	
Dimension	Height 1.7" (43mm), Width 17.2" (437mm), Depth 28.5" (724mm)
<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit</p> <p>www.tyronesystems.com</p>	