

Tyrone Camarero Specifications

Tyrone

Camarero SS200T3R-13



Key features

- Single socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family
- Up to 512GB ECC DDR3, up to 1866MHz; 8x DIMM sockets
- 2x M2075 GPU cards pre-installed, 1 (x8) PCI-E 3.0 low-profile slot
- Integrated IPMI 2.0 with KVM and Dedicated LAN
- Intel® I350 Dual-Port GbE Controller
- 3x Hot-swap 3.5" Drive Bays
- 1400W High-efficiency Power Supply 80Plus Platinum Level (94%+)
- 8x Counter rotating fans w/ optimal fan speed control
- Smart server management tools

Processor/Cache

Processor Single socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family

Chipset

Intel® C602 Chipset

System Memory

8x 240-pin DDR3 DIMM sockets Up to 512GB DDR3 ECC LRDIMM Up to 256GB DDR3 ECC Registered memory (RDIMM)

Expansion Slots

PCI-Express 2 (x16) PCI-E 3.0 slots (GPU cards opt.)
1 (x8) PCI-E 3.0 slot for I.B. Card

Integrated On-Board

SATA Intel ICH10R SATA 3.0Gbps Controller
RAID 0, 1, 5, 10 support

LAN 2 RJ45 Gigabit Ethernet LAN ports 1 RJ45
Dedicated IPMI LAN port

Add-on Options

RAID Optional

Optical Drive None

Front Panel :

LED Indicators Power LED/ Hard drive activity LED/
2x Network activity LEDs
/System Overheat LED

Switches Power On/Off Button

Drive bays

HDD bays 3x 3.5" Hot-swap drive bays

Peripheral Bays Optional

Power Supply

1400W High-efficiency Power Supply 80Plus Platinum Level (94%+)

Cooling System

8x counter-rotating fans with optimal fan Speed control

Form Factor

1U Rackmount , Height 1.7" (43mm), Width 17.2" (437mm),
Depth 28.2" (716mm)

Email : info@tyronesystems.com

For more/current product information, visit

www.tyronesystems.com