

Tyrone Camarero Specifications

Tyrone

Camarero SS2C0T3R-11

Key features

- Single socket H2 (LGA 1155) supports Intel® Xeon® E3-1200 & v2 series, 2nd Gen Core i3 processors*
- Intel® C202 PCH Chipset
- 1x 3.5" or optional 2x 2.5" internal SATA2 hard drive bays
- 1x PCI-E 3.0* x8 Low-profile slot
- Up to 32GB DDR3 ECC 1333MHz / 1600MHz* UDIMMs in 4 sockets
- Intel® 82579LM and 82574L, 2x Gigabit Ethernet LAN ports
- IPMI 2.0 on Dedicated LAN port
- 200W Low-noise power supply w/ PFC
- Disk-on-module (DOM) power connector



Processor/Cache

Processor Intel® Xeon® processor E3-1200 & v2 series, Intel® 2nd Gen Core i3 processors

System Bus

Chipset

Intel® C202 PCH chipset

System Memory

Memory Capacity 4x 240-pin DDR3 DIMM sockets
Supports up to 32 GB DDR3 ECC Un-Buffered memory (UDIMM)

Expansion Slots

PCI-Express 1x PCI-E 3.0* x8 Low-profile slot

Integrated On-Board

SATA 6x SATA2 (3Gbps) w/ RAID 0, 1, 5, 10

LAN 2x RJ45 LAN ports 1x RJ45 Dedicated IPMI LAN port

Add-on Options

RAID Optional
Optical drive Optional

Front Panel :

LED Indicators Power LED / Hard drive activity LED /2x Network activity LEDs / System Overheat LED

Switches Power On/Off Button

Drive bays

HDD bays 1x 3.5" or optional 2x 2.5" internal SATA2 hard drive bays

Peripheral Bays Optional

Power Supply

200W Low-noise power supply w/ PFC

Cooling System

2x 8500 RPM 40x28mm PWM cooling fans

Form Factor

1U Rackmount, Height – 1.7" (43mm), Width - 17.2" (437mm), Depth - 11.3" (287mm)

Email : info@tyronesystems.com

For more/current product information, visit www.tyronesystems.com