


Tyrone Camarero Specifications



Camarero SS2C0T3U-14R

Key features

- Single socket H2 (LGA 1155) supports Intel® Xeon® E3-1200 & v2 series, 2nd & 3rd Gen Core i3 processors
- Intel® C216 Express PCH chipse
- 4x 3.5" Hot-swap SATA2 HDDs s
- 1 PCI-E 3.0 x16, 2 PCI-E 2.0 x4 in x8 (UIO) management (IPMI 2.0)
- Up to 32GB DDR3 ECC 1333MHz /1600MHz UDIMMs in 4 sockets
- Intel® 82574L Dual port GbE LAN
- I/O ports: 2x GbE LAN, 1x Dedicated LAN for IPMI Remote Management, 1x VGA, 1x COM, 2x PS/2, 2x USB
- 4x 4cm Counter-rotating PWM fans
- 500W Redundant High-Efficiency Platinum Level Power Supplies



Processor/Cache

Processor Single socket H2 (LGA 1155) supports Intel® Xeon® E3-1200 & v2 series, 2nd & 3rd Gen Core i3 processors

Chipset

Intel® C216 PCH chipset

System Memory

Memory Capacity 4x 240-pin DDR3 DIMM sockets Supports up to 32 GB DDR3 ECC Un-Buffered memory (UDIMM)

Expansion Slots

PCI-Express 1x PCI-E 3.0 x16 2x PCI-E 2.0 x4 (in x8) (UIO)

Integrated On-Board

SATA 2x SATA 3.0 (3Gbps) w/ RAID 0, 1, 5, 10
4x SATA 2.0 (3Gbps) w/ RAID 0, 1, 5, 10

LAN 2x RJ45 LAN ports 1x RJ45 Dedicated IPMI LAN port

Add-on Options

RAID Optional
Optical Drive Optional

Front Panel :

LEDs Power LED,Hard drive activity LED,2x Network activity LEDs,System Overheat LED,Information LED (temp, status)
Buttons Power On/Off button,System Reset button Universal Identification (UID) button

Drive bays

HDD bays 4x 3.5" Hot-swap SATA2 HDDs
Peripheral Bays Optional

Power Supply

500W Redundant High-Efficiency,Power Supplies (80Plus Platinum Level Certified)

Cooling System

4x 4cm Counter-rotating PWM fans

Form Factor

1U Rackmount
Height 1.7" (43mm),
Width 17.2" (437mm),
Depth 25.6" (650mm)

Email : info@tyronesystems.com

For more/current product information, visit
www.tyronesystems.com