

Tyrone Camarero Specifications



Camarero SS2R0T3R-14

Key features

- Single socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600/1600 v2 family
- Intel® C602 Chipset
- 4x 3.5" Hot-swap drive bays
- Up to 256GB RDIMM or 64GB UDIMM; DDR3 up to 1600MHz; 8x DIMM sockets
- 1x PCI-E 3.0 x16 FH expansion slot
- Intel® i350 Dual Port Gigabit Ethernet
- Integrated IPMI 2.0 and KVM with Dedicated LAN
- SATA2 w/ RAID 0, 1, 10 (R5 option)
- 350W Gold Level Power Supply
- SATA Disk-on-module (DOM) power connector; TPM 1.2 and USB Type A



Processor/Cache	
Processor	Single socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600/1600 v2 family
Chipset	
Intel® C602 Chipset	
System Memory	
Memory Capacity	8x 240-pin DDR3 DIMM sockets Supports up to 256 GB DDR3 ECC
Expansion Slots	
PCI-Express	1x PCI-E 3.0 x16 Full-height slot
Integrated On-Board	
SATA	2 SATA3 (6Gbps) & 4 SATA2 (3Gbps) RAID 0, 1, 5, 10 support (Windows) RAID 0, 1, 10 support (Linux)
LAN	2 RJ45 Gigabit Ethernet LAN ports 1 RJ45 Dedicated IPMI LAN port
Add-on Options	
RAID Card	Optional
Optical Drive	Optional

Front Panel :	
LED Indicators	Power status LED HDD activity LED 2x Network activity LEDs Universal Information (UID) LED
Switches	Power On/Off Button, System Reset Button
Drive bays	
HDD bays	4x 3.5" Hot-swap drive bays
Peripheral Bays	Optional
Power Supply	
350W AC power supply w/ PFC	
Cooling System	
4x 40x28mm 4-pin PWM Cooling Fans	
Form Factor	
1U Rackmount	
Height	1.7" (43mm)
Width	17.2" (437mm)
Depth	19.8" (503mm)
<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit</p> <p>www.tyronesystems.com</p>	