

# Tyrone Camarero Specifications



## Camarero SS2R0T3R-14R

### Key features

- Single socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600/1600 v2 family
- Intel® C602 Chipset
- 4x 3.5" Hot-swap drive bays
- Up to 512GB ECC DDR3, up to 1866MHz; 8x DIMM slots
- 1x PCI-E 3.0 x16 FH expansion slot
- Intel® i350 Dual Port Gigabit Ethernet
- Integrated IPMI 2.0 and KVM with Dedicated LAN
- SATA2 w/ RAID 0, 1, 10 (R5 option)
- 400W (1+1) Redundant Short-depth high-efficiency power supplies
- SATA Disk-on-module (DOM) power connector; TPM 1.2 and USB Type A



Processor/Cache	
Processor	Single socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600/1600 v2 family
Chipset	
Intel® C602 Chipset	
System Memory	
Memory Capacity	8x 240-pin DDR3 DIMM sockets Supports up to 256 GB DDR3 ECC
Expansion Slots	
PCI-Express	1x PCI-E 3.0 x16 Full-height slot
Integrated On-Board	
SATA	2 SATA3 (6Gbps) & 4 SATA2 (3Gbps) RAID 0, 1, 5, 10 support (Windows) RAID 0, 1, 10 support (Linux)
LAN	2 RJ45 Gigabit Ethernet LAN ports 1 RJ45 Dedicated IPMI LAN port
Add-on Options	
RAID Card	Optional
Optical Drive	Optional

Front Panel :	
LED Indicators	Power status LED HDD activity LED 2x Network activity LEDs System Overheat LED
Switches	Power On/Off Button, System Reset Button
Drive bays	
HDD bays	4x 3.5" Hot-swap drive bays
Peripheral Bays	Optional
Power Supply	
400W (1+1) Redundant SuperCompact Short-depth AC-DC high-efficiency power supply with PMBus and I2C	
Cooling System	
4x 40x28mm 4-pin PWM Cooling Fans	
Form Factor	
1U Rackmount	
Height	1.7" (43mm)
Width	17.2" (437mm)
Depth	19.85" (503mm)
<p><b>E : <a href="mailto:info@tyronesystems.com">info@tyronesystems.com</a></b></p> <p><b>For more/current product information, visit <a href="http://www.tyronesystems.com">www.tyronesystems.com</a></b></p>	