

Tyrone Camarero Specifications

Tyrone[®]

Camarero SS2ROT3R-34

Key features

- Single socket R (LGA 2011) supports Intel® Xeon® processor E5-2600/1600 and E5-2600/1 v2 family
- Up to 512GB ECC DDR3, up to 1866MHz; 8x DIMM sockets
- Expansion slots: 2 PCI-E 3.0 x16, 1 PCI-E 3.0 x4 (in x8), 1 PCI-E 2.0 x4 (in x8), 1x PCI-32
- Intel® 82579LM and 82574L, 2x Gigabit Ethernet LAN ports
- Intel® i350 Dual Port Gigabit
- 4 USB 3.0 and 14 USB 2.0 ports
- 4x 3.5" SATA3 HDD bays, 90° rotating hard drive cage, 4x 2.5" internal HDD/SSD bays (opt.)
- 900W Gold Level Power Supply



Processor/Cache	
Processor	Single socket R (LGA 2011) supports Intel® Xeon® processor E5-2600/1600 and E5-2600/1600 v2 family
Chipset	
	Intel® C602 Chipset
System Memory	
	8x 240-pin DDR3 DIMM slots, Up to 512GB DDR3 ECC LRDIMM, Up to 256GB DDR3 ECC RDIMM, Up to 64GB DDR3 ECC/non-ECC UDIMM
Expansion Slots	
PCI-Express	2 PCI-E 3.0 x16, 1 PCI-E 3.0 x4 (in x8), 1 PCI-E 2.0 x4 (in x8), 1x PCI-32
Integrated On-Board	
SATA	2 SATA3 (6Gbps) and 4 SATA2 (3Gbps) RAID 0, 1, 5, 10
LAN	2x RJ45 LAN ports

Front Panel	
LED Indicators	Power LED Hard drive activity LED Network activity LED System Overheat LED
Buttons	Power On/Off button System Reset button
Drive bays	
HDD bays	4x 3.5" SATA3 HDD bays, 4x 2.5" internal HDD/SSD bays (opt.)
Power Supply	
	900W Gold Level Power Supply
Cooling System	
	1x 12cm rear exhaust fan Optimized Cooling Technology at 21dB Whisper-Quiet Operation
Form Factor	
	Mid- Tower
Height	16.7" (424 mm),
Width	7.6" (193 mm),
Depth	20.68" (525.3 mm)
<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit</p> <p>www.tyronesystems.com</p>	