

Tyrone Camarero Specifications



Camarero SS2R0T6C-32R

Key features

- Single socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family
- 2x 3.5" Hot-swap SATA3 (6 Gbps)
- 1x (x8) PCI-E 3.0 low-profile slot
- Up to 128GB DDR ECC RDIMM or 32GB DDR ECC UDIMM; 4x DIMMs
- 2x GbE LAN ports via Intel® i350
- 1x Dedicated LAN for IPMI Remote Management
- 4x 8cm Heavy duty fans with optimal cooling zone
- 1620W Redundant 80Plus Platinum Level power supplies



Processor/Cache	
Processor	Single socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family
Chipset	
Intel® C602J Chipset	
System Memory	
Memory Capacity	4x 240-pin DDR3 DIMM sockets Supports up to 128 GB DDR3 ECC
Expansion Slots	
PCI-Express	1 (x8) PCI-E 3.0 Low-profile slot
Integrated On-Board	
SATA RAID 0, 1	1x SATA DOM SATA 3.0 6Gbps with
LAN	2 RJ45 Gigabit Ethernet LAN ports 1 RJ45 Dedicated IPMI LAN port
Add-on Options	
RAID Card	Optional

Front Panel :	
LED Indicators	Power LED, Node status LED
Switches	Power On/Off Button
Drive bays	
HDD bays	2x 3.5" hot-swap SATA3 (6Gbps) HDDs per node; up to 16 HDDs total Enterprise SATA HDD only recommended
Power Supply	
1620W high-efficiency redundant power supply w/ PMBus	
Cooling System	
4x 8cm 11K RPM, 4-pin PWM cooling fans	
Form Factor	
3U Rackmount	
Height	5.21" (132.5 mm)
Width	17.26" (438.4 mm)
Depth	23.2" (589 mm)
<p>E : info@tyronesystems.com</p> <p>For more/current product information, visit</p> <p>www.tyronesystems.com</p>	