

Tyrone Camarero Specifications

Tyrone[®]

Camarero SS30012E1-212R

Key features

- Single socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600 v4/ v3 family
- Intel® C612 chipset
- Up to 1TB ECC 3DS LRDIMM , up to DDR4- 2400MHz ; 8x DIMM slots
- 1 PCI-E 3.0 x8 (in x16), 2 PCI-E 3.0 x8 1 PCI-E 3.0 x8 (in x16), 1 PCI-E 2.0 x2 (in x4), 1 PCI-E 2.0 x4 (in x8)
- Intel® i350-AM4 Quad port GbE LAN
- 12x 3.5" Hot-swap SAS3 HDD bays; Opt. 2x 2.5" Hot-swap HDD bays (rear)
- SAS3 via LSI 3008 controller; IR mode
- Server remote management: IPMI 2.0 / KVM over LAN / Media over LAN
- 3x 8cm high-performance PWM fans
- 920W Redundant Power Supplies Platinum Level (94%)
- Dual JBOD expansion ports



Processor/Cache		Front Panel	
Processor	Single socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600 v4/ v3 family	LED Indicators	Power status LED,HDD activity LED, 2x Network activity LEDs,System Overheat LED,Power fail LED
		Buttons	Power On/Off button,System Reset button
Chipset		Drive Bays	
Chipset	Intel® C612 chipset	HDD bays	12x 3.5" Hot-swap SAS3 HDD bays
		Optional	2x 2.5" Hot-swap HDD bays (rear)
System Memory		Power Supply	
Memory Capacity	8x 288-pin DDR4 DIMM slots,Up to 1TB ECC 3DS LRDIMM,Up to 512GB ECC LRDIMM,Up to 256GB ECC RDIMM		920W Redundant Power Supplies Platinum Level (94%)
Expansion Slots		Cooling System	
PCI-Express	1x PCI-E 3.0 x4 (in x8) slot,1x PCI-E 3.0 x8 (in x16) slot,2x PCI-E 3.0 x8 slots,1x PCI-E 2.0 x2 (in x4) slot,1x PCI-E 2.0 x4 (in x8) slot		3x 8cm 9.5K RPM, 4-pin PWM fans
Integrated On-Board		Form Factor	
SAS	SAS3 (12Gbps) via LSI 3008 (IR mode) SW RAID 0, 1, 10	Form Factor	2U Rackmount
LAN	4x RJ45 Gigabit Ethernet LAN ports, 1x RJ45 Dedicated IPMI LAN port	width:	17.2" (437mm),
		Height:	3.5" (89mm),
		Depth:	25.6" (648mm)
Add-on Options		<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit</p> <p>www.tyronesystems.com</p>	
Optical Drive	None		