

Tyrone Camarero Specifications

Tyrone[®]

Camarero SS300T3-14L4

Key features

- Single socket H3 (LGA 1150) supports Intel® Xeon® E3-1200 v3, 4th gen. Core i3, Pentium, Celeron processors
- Intel® C224 Express PCH
- 4x 3.5" Hot-swap SATA3 HDDs
- 1x PCI-E 3.0 x16 Full-height slot
- Up to 32GB DDR3 ECC 1600MHz UDIMMs in 4 sockets
- Dual Gigabit Ethernet LAN ports (1x Intel® i217LM & 1x Intel® i210AT)
- IPMI 2.0 on Dedicated LAN port
- 350W Gold Level Power Supply



Processor/Cache		Front Panel :	
Processor	Single socket H3 (LGA 1150) supports Intel® Xeon® E3-1200 v3, 4th gen. Core i3, Pentium, Celeron processors	LED Indicators	Power LED Hard drive activity LED 4x Network activity LEDs System Overheat LED
		Switches	Power On/Off button System Reset button
Chipset		Drive bays	
Intel® C224 Express PCH		HDD bays	4x 3.5" Hot-swap SATA3 HDDs w/ RAID
		Peripheral Bays	Slim optical drive (optional)
System Memory		Power Supply	
Memory Capacity	4x 240-pin DDR3 DIMM sockets Supports up to 32 GB DDR3 ECC Un-Buffered memory (UDIMM))	350W Gold Level Power Supply	
Expansion Slots		Cooling System	
PCI-Express	1x PCI-E 3.0 x16 Full-height slot	4x 4cm 12,500 RPM PWM fans Optional fans to cool add-on cards	
Integrated On-Board		Form Factor	
SATA	SATA3 (6Gbps) w/ RAID 0, 1, 10, 5. SATA2 (3Gbps) w/ RAID 0, 1	1U Rackmount	
LAN	DOM Power Connector 2x RJ45 LAN ports , 1x RJ45 Dedicated IPMI LAN port	Width- 17.2" (437mm), Height- 1.7" (43mm) , Depth – 14.5" (369mm)	
Add-on Options		<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit</p> <p>www.tyronesystems.com</p>	
RAID Card	Optional		
Optical Drive	Optional		