

# Tyrone Camarero Specifications

**Tyrone**<sup>®</sup>

## Camarero SS300T3R-14R

### Key features

- Single socket H3 (LGA 1150) supports Intel® Xeon® E3-1200 v3/v4, 4th gen. Core i3, Pentium, Celeron processors
- Intel® C224 Express PCH
- 4x 3.5" Hot-swap SATA3 HDD bays
- 1x PCI-E 3.0 x8 (in x16) Full-height slot
- Up to 32GB DDR3 ECC 1600MHz UDIMMs in 4 sockets
- Dual Gigabit Ethernet LAN ports (1x Intel® i217LM & 1x Intel® i210AT)
- IPMI 2.0 on Dedicated LAN port
- 400W Redundant Power Supplies Optional Battery Backup Power (BBP®)



Processor/Cache	
Processor	Single socket H3 (LGA 1150) supports Intel® Xeon® E3-1200 v3/v4, 4th gen. Core i3, Pentium, Celeron processors
Chipset	
Intel® C224 Express PCH	
System Memory	
Memory Capacity	4x 240-pin DDR3 DIMM sockets Supports up to 32 GB DDR3 ECC Un-Buffered memory (UDIMM)
Expansion Slots	
PCI-Express	1x PCI-E 3.0 x8 (in x16) Full-height slot
Integrated On-Board	
SATA	SATA3 (6Gbps) w/ RAID 0, 1, 10, 5 SATA2 (3Gbps) w/ RAID 0, 1
LAN	2x RJ45 LAN ports 1x RJ45 Dedicated IPMI LAN port
Add-on Options	
RAID Card	Optional
Optical Drive	Optional

Front Panel :	
LED Indicators	Power LED Hard drive activity LED 2x Network activity LEDs System Overheat LED
Switches	Power On/Off button System Reset button
Drive bays	
HDD bays	4x 3.5" Hot-swap SATA3 HDDs w/ RAID
Peripheral Bays	Slim optical drive (optional)
Power Supply	
400W Redundant Power Supplies Optional Battery Backup Power (BBP®)	
Cooling System	
4x 4cm 12,500 RPM PWM fans Optional fans to cool add-on cards	
Form Factor	
1U Rackmount	Width- 17.2" (437mm) , Height- 1.7" (43mm) , Depth – 19.8" (503mm)
<p><b>Email : <a href="mailto:info@tyronesystems.com">info@tyronesystems.com</a></b></p> <p><b>For more/current product information, visit</b></p> <p><b><a href="http://www.tyronesystems.com">www.tyronesystems.com</a></b></p>	