

Tyrone Camarero Specifications

Tyrone[®]

Camarero SS300T3R-34



Key features

- Single socket H3 (LGA 1150) support Intel® Xeon® E3-1200 v3, 4th gen. Core i3/i5/i7 processors
- Intel® C226 Express PCH
- Up to 32GB DDR3 ECC/non-ECC 1600MHz UDIMM in 4 sockets
- 2x PCI-E 3.0 x16 (x16/NA or x8/x8), 3x PCI-E 2.0 x1, 2x PCI 32-bit slots
- I/O Ports: 1 DVI, 1 VGA, 1 HDMI, 1 display port, triple display capable, ALC1150 HD Audio, 2 COM, 2 GbE LAN, 2 USB 3.0 + 2 USB 2.0 (front)
- 4x 3.5" internal SAS/SATA HDD Bays 90° rotatable HDD cage design
4x 2.5" internal SAS/SATA HDD (opt.)
- 500W High Efficiency Power Supply

Processor/Cache	
Processor	Intel® Xeon® E3-1200 v3, 4th gen. Core i3/i5/i7 processors
Chipset	
	Intel® C226 Express PCH
System Memory	
Memory Capacity	4x 240-pin DDR3 DIMM sockets Supports up to 32GB DDR3 ECC/Non-ECC Un-Buffered memory (UDIMM)
Expansion Slots	
PCI-Express	2x PCI-E 3.0 x16 (x16/NA or x8/x8), 3x PCI-E 2.0 x1, 2x PCI 32-bit slots
Integrated On-Board	
SATA	SATA3 via PCH w/ RAID 0, 1, 5, 10 SATA3 via ASM1061®
LAN	2x RJ45 Gigabit Ethernet LAN ports
Add-on Options	
Raid card	Optional
Optical Drive	Optional

Front Panel :	
LED Indicators	Power LED, Hard drive activity, Network activity LED, System Overheat LED
Switches	Power On/Off button
Drive bays	
HDD bays	4x 3.5" SAS/SATA HDD Bays. Enterprise SATA HDD only recommended
Peripheral Bays	2x 5.25" peripheral drive bays
Power Supply	
	500W High Efficiency Power Supply
Cooling System	
	1x 12cm rear exhaust fan with Optimal Fan Speed Control, Optimized cooling technology for Whisper-Quiet Operation
Form Factor	
	Mid- Tower
Height	16.7" (424mm),
Width	7.6" (193mm),
Depth	20.68" (525.3mm)
<p>Email: info@tyronesystems.com</p> <p>For more/current product information, visit www.tyronesystems.com</p>	