

Tyrone Camarero Specifications

Tyrone[®]

Camarero SS300T6R-34



Key features

- Single socket H3 (LGA 1150) supports Intel® Xeon® E3-1200 v3, 4th gen. Core i3, Pentium V, Celeron processors
- Intel® C222 Express PCH
- Up to 32GB DDR3 ECC 1600MHz UDIMMs in 4 sockets
- 1 (x8) PCI-E 3.0 in x16, 1 (x8) PCI-E 3.0, and 1 (x4) PCI-E 2.0 in x8 slots
- I/O Ports: 1 VGA, 2 COM, 2 GbE LAN, dedicated IPMI, 2 USB 2.0 (front)
- 4x 3.5" tool-less HDD trays + 2x 5.25" drive bays
- 300W High-efficiency Power Supply/500W AC power supply w/ PFC

Processor/Cache	
Processor	Intel® Xeon® processor E3-1200 v3 and 4th Gen Core i3, Pentium, Celeron processors
Chipset	
	Intel® C222 Express PCH
System Memory	
Memory Capacity	4x 240-pin DDR3 DIMM sockets, Supports up to 32 GB DDR3 ECC Un-Buffered memory (UDIMM)
Expansion Slots	
PCI-Express	1 (x8) PCI-E 3.0 in x16 slot, 1 (x8) PCI-E 3.0 slot, 1 (x4) PCI-E 2.0 in x8 slot
Integrated On- Board	
SATA	SATA3 (6Gbps) w/ RAID 0, 1. SATA2 (3Gbps) w/ RAID 0, 1, 5, 10
LAN	2x RJ45 Gigabit Ethernet LAN ports 1x RJ45 Dedicated IPMI LAN port
Add-on Options	
RAID Card	Optional
Optical Drive	None

Front Panel :	
Buttons	Power On/Off button
LEDs	Power LED, Hard drive activity LED, Network activity LED, System Overheat LED
Ports	2x Front side USB ports
Drive bays	
HDD bays(Internal)	4x 3.5" tool-less HDD trays, Enterprise SATA HDD only recommended
HDD(External)	2x 5.25" external drive bays
Power Supply	
	300W High-efficiency Power Supply/500W AC power supply w/ PFC
Cooling System	
	1x 9cm (rear) PWM fan w/ tool-less design 1x 8cm (front) cooling fan (optional), Optimized Cooling Technology at 25dB Whisper-Quiet Operation
Form Factor	
	Mid Tower Width- 7.25" (184mm) , Height- 14.25" (362mm) , Depth – 16.75" (425mm)
<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit www.tyronesystems.com</p>	