

Tyrone Camarero Specifications

Tyrone[®]

Camarero SS300TR-310

Key features

- Single socket H4 (LGA 1151) supports Intel® 6th Gen. Core™ i7/i5/i3 series
- Intel® Z170 Express Chipset
- Up to 64GB Non-ECC UDIMM, DDR4-3200MHz (OC), in 4 DIMM slots
- 2 PCI-E 3.0 x16 (1 x16 or dual x8), 1 PCI-E 3.0 x16 (x4), 1 PCI-E 3.0 x4, 2 PCI-E 3.0 x1 (in x4) slots
- 1 PCIe M.2; PCIe x4 2260/2280/22110
- I/O Ports: 1 GbE LAN, 2 USB 3.0 (front)
- Removable 3.5" and 2.5" HDD/SSD cages with tool-less trays for up to 10 drives; 2x 5.25" Peripheral Drive Bays
- 1 DVI-D, 1 DP (Display Port), 1 HDMI
- HD Audio 7.1 channel connector by Realtek ALC1150
- 750W Multi-output Power Supply



Processor/Cache		Front Panel	
Processor	Single socket H4 (LGA 1151) supports Intel® 6th Gen. Core™ i7/i5/i3 series	LED Indicators	HDD activity LED, Power Status LED
Chipset	Intel® Z170 Express Chipset	Buttons	Power On/Off button, System Reset Button
System Memory		Drive Bays	
Memory Capacity	4x 288-pin DDR4 DIMM slots, Supports up to 64GB DDR4 Non-ECC Un-Buffered memory (UDIMM) in 4 DIMM slots	HDD Bays (Internal)	3.5" and 2.5" HDD/SSD cages with tool-less trays for up to 10 drives
Expansion Slots	2 PCI-E 3.0 x16 (1 x16 or dual x8), 1 PCI-E 3.0 x16 (x4), 1 PCI-E 3.0 x4, 2 PCI-E 3.0 x1 (in x4) slots	Peripheral Bays	2x 5.25" Peripheral Drive Bays
Integrated On-Board	SATA3 via PCH w/ RAID 0, 1, 5, 10	Power Supply	
LAN	1x RJ45 Gigabit Ethernet LAN port	750W Multi-output Power Supply	
Add-on Options		Cooling System	
Raid	Optional	3x 12cm PWM fans	
Optical Drive	Optional	Form Factor	
		Form Factor	Mid-Tower
		Width:	7.9" (201mm),
		Height:	18.1" (460mm),
		Depth:	19.4" (493mm)
		<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit</p> <p>www.tyronesystems.com</p>	