Tyrone Camarero Specifications

Ivrone

Camarero SS300TW-12R

Key features

- Single socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600 v4/v3 and E5-1600 v4/v3 family
- Intel® C612 chipset
- Up to 1TB ECC 3DS LRDIMM, up to DDR4- 2400 MHz; 8x DIMM slots
- 2x PCI-E 3.0 x16 Left Riser slot: 1x PCI-E 3.0 x8 LP slot
- Intel® i350-AM2 Dual port GbE LAN
- Integrated IPMI 2.0 and KVM with Dedicated LAN
- 2x 2.5" fixed drive bays
- 400W Redundant Power Supplies Platinum Level Certified







Processor/Cache

Single socket R3 (LGA 2011) supports Processor

Intel® Xeon® processor E5-2600 v4/ v3 and E5-1600 v4/ v3 family

Chipset

Intel® C612 chipset Chipset

System Memory

Memory Capacity 8x 288-pin DDR4 DIMM slots,

Up to 1TB ECC 3DS LRDIMM, Up to 512GB ECC LRDIMM, Up to 256GB ECC RDIMM

Expansion Slots

PCI-Express Left Riser: 2x PCI-E 3.0 x16 slots,

1x PCI-E 3.0 x8 LP slot

Integrated On-Board

SATA SATA3 (6Gbps) via C612 controller,

> RAID 0, 1, 10 support; 5 supported under Windows

LAN 2x RJ45 Gigabit Ethernet LAN ports,

1x RJ45 Dedicated IPMI LAN port

Add-on Options

Optional Raid

Optical Drive None

Front Panel

LED Indicators Power LED, Hard drive activity LED,

> 2x Network activity LEDs, System Overheat LED

Power On/Off button, System Reset button **Buttons**

Drive Bays

HDD bays 2x 2.5" fixed drive bays

Power Supply

400W Redundant Power Supplies Platinum Level Certified

Cooling System

4x 40x56mm PWM Cooling Fans, 2x Optional fans for AOC cooling

Form Factor

Form Factor 1U Rackmount

Height : 1.7" (43mm), Width 17.2" (437mm), 16.9" (429mm) Depth

Email: info@tyronesystems.com

For more/current product information, visit www.tyronesystems.com