

Tyrone Camarero Specifications

Tyrone[®]

Camarero SS300TW-14R

Key features

- Single socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600v4/ v3 and E5-1600 v3 family
- Intel® C612 chipset
- 4x 3.5" Hot-swap SATA3 drive bays
- 1x Slim DVD-ROM drive bay
- Up to 1TB ECC 3DS LRDIMM , up to DDR4- 2400MHz ; 8x DIMM slots
- 2x PCI-E 3.0 x16 FHFL, 1x PCI-E 3.0 x8 LPHL (3x AOC slots total)
- Intel® i350-AM2 Dual port GbE LAN
- Integrated IPMI 2.0 and KVM with Dedicated LAN
- I/O ports: 1x VGA, 2x COM, 2x USB 3.0, 2x USB 2.0
- 500W Redundant Power Supplies Platinum Level (94%+)



Processor/Cache		Front Panel	
Processor	Single socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600v4/ v3 and E5-1600 v3 family	LED Indicators	Power LED, Hard drive activity LED, 2x Network activity LEDs, System Overheat LED
		Buttons	Power On/Off button, System Reset button
Chipset		Drive Bays	
Chipset	Intel® C612 chipset	HDD bays	4x 3.5" Hot-swap drive bays
		Peripheral Bays	1x slim DVD-ROM drive bay
System Memory		Power Supply	
Memory Capacity	8x 288-pin DDR4 DIMM slots, Up to 1TB ECC 3DS LRDIMM, Up to 512GB ECC LRDIMM, Up to 256GB ECC RDIMM		500W Redundant Power Supplies Platinum Level (94%+)
Expansion Slots		Cooling System	
PCI-Express	2x PCI-E 3.0 x16 FHFL, 1x PCI-E 3.0 x8 LPHL (3x AOC slots total)		4x 40x28mm 4-pin PWM Cooling Fans
Integrated On-Board		Form Factor	
SATA	SATA3 (6Gbps) via C612 controller RAID 0, 1, 10 support; 5 supported under Windows	Form Factor	1U Rackmount
LAN	2x RJ45 Gigabit Ethernet LAN ports, 1x RJ45 Dedicated IPMI LAN port	Height	: 1.7" (43mm),
		Width	: 17.2" (437mm),
		Depth	: 25.6" (650mm)
Add-on Options		<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit</p> <p>www.tyronesystems.com</p>	
Raid Card	Optional		