

Tyrone Camarero Specifications

Camarero SS300TZ-34

Key features

- Single socket H4 (LGA 1151) supports Intel® 6th Gen. Core™ i7/i5/i3 series. Intel® Celeron® and Intel® Pentium®
- Intel® Z170 Express Chipset
- Up to 64GB Non-ECC UDIMM, DDR4-3200MHz (OC), in 4 DIMM slots
- Single Gigabit Ethernet LAN port (Intel® i219V)
- 6 SATA3 (6Gbps); RAID 0, 1, 5, 10
- 2 PCI-E 3.0 x16 (1 x16 or dual x8), 1 PCI-E 3.0 x16 (x4), 1 PCI-E 3.0 x4, 2 PCI-E 3.0 x1 (in x4) slots
- 1 PCIe M.2 (support PCIe x4 only, 2260/2280/22110)
- 6 USB 3.0 (2 rear + 4 via header), 6 USB 2.0 (2 rear + 4 via headers), 1 USB 3.1 (10Gbps) Type C (rear)
- 1 DVI-D, 1 DP (Display Port), 1 HDMI
- HD Audio 7.1 channel connector by Realtek ALC1150
- UEFI BIOS support
- 4x 3.5" internal SAS/SATA HDD Bays. 4x 2.5" internal SAS/SATA HDD (opt.)
- Peripheral Drive Bays: 2x 5.25" and 1x 3.5"
- High Efficiency Power Supply
- Cost Effective Desktop, Embedded, Workstation Chassis
- 500W AC power supply w/ PFC

Tyrone®



SC73202 front I/O:
2x USB 3.0 ports,
2x HD/Audio ports



Processor/Cache		Front Panel	
Processor	Single socket H4 (LGA 1151) supports Intel® 6th Gen. Core™ i7/i5/i3 series. Intel® Celeron® and Intel® Pentium®	LED Indicators	Power status LED, Hard drive activity LED, Network activity LED, System Overheat LED
Chipset	Intel® Z170 Express Chipset	Buttons	Power On/Off button
System Memory		Drive Bays	
Memory Capacity	4x 288-pin DDR4 DIMM slots, Supports up to 64GB DDR4 Non-ECC, Un-Buffered memory (UDIMM) in 4 DIMM slots	HDD bays	4x 3.5" internal SAS/SATA HDD Bays. 4x 2.5" internal SAS/SATA HDD (opt.)
Expansion Slots	2 PCI-E 3.0 x16 (1 x16 or dual x8), 1 PCI-E 3.0 x16 (x4), 1 PCI-E 3.0 x4, 2 PCI-E 3.0 x1 (in x4) slots	Peripheral Bays	2x 5.25" and 1x 3.5"
Integrated On-Board		Power Supply	
SATA	SATA3 via PCH w/ RAID 0, 1, 5, 10	500W AC power supply w/ PFC	
LAN	1x RJ45 Gigabit Ethernet LAN port	Cooling System	
Add-on Options		1x 12cm (1850rpm) rear exhaust fan. 1x 12cm (1850rpm) front cooling fan (opt.). Optimized Cooling Technology at 21dB. Whisper-Quiet Operation	
Raid	Optional	Form Factor	
Optical Drive	Optional	Form Factor	Mid-Tower
		Width:	7.6" (193 mm),
		Height:	16.7" (424 mm),
		Depth:	20.68" (525.3 mm)
		<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit</p> <p>www.tyronesystems.com</p>	