

Tyrone Camarero Specifications

Tyrone[®]

Camarero SS3C0TR-14

Key features

- Single socket H3 (LGA 1150) supports Intel® Xeon® E3-1200 v3/v4, 4th gen. Core i3, Pentium, Celeron processors
- Intel® C222 Express PCH
- Up to 32GB DDR3 ECC 1600MHz UDIMMs in 4 sockets
- Dual Gigabit Ethernet LAN ports (1x Intel® i217LM & 1x Intel® i210AT)
- 2x SATA (6Gbps), 4x SATA (3Gbps)
- 1x PCI-E 3.0x8 slots
- 2x USB 3.0 (1 Type-A + 1 via header) 6x USB 2.0 (4 rear + 2 via header)
- 4x 3.5" Hot-swap SAS / SATA Drive Bays
- 1x Slim DVD ROM Drive (Optional)
- Integrated IPMI 2.0 with KVM and Dedicated LAN
- SATA DOM power connector support
- VGA D-sub connector, TPM header
- 350W High-efficiency Power Supply Gold Level



Processor/Cache		Front Panel	
Processor	Single socket H3 (LGA 1150) supports Intel® Xeon® E3-1200 v3/v4, 4th gen. Core i3, Pentium, Celeron processors	LED Indicators	Power LED, Hard drive activity LED, 2x Network activity LEDs, System Overheat LED
		Buttons	Power On/Off button, System Reset button
Chipset		Drive Bays	
Chipset	Intel® C222 Express PCH	HDD bays	4x 3.5" Hot-swap SAS / SATA Drive Bays
		DVD-ROM	1x Slim DVD ROM Drive (Optional)
System Memory		Power Supply	
Memory Capacity	4x 240-pin DDR3 DIMM sockets, Supports up to 32 GB DDR3 ECC, Un-Buffered memory (UDIMM)		350W High-efficiency Power Supply Gold Level
Expansion Slots		Cooling System	
PCI-Express	1x PCI-E 3.0x8 slots		4x 4cm 12,500 RPM PWM fans
Integrated On-Board		Form Factor	
SATA	SATA3 (6Gbps) w/ RAID 0, 1, SATA2 (3Gbps) w/ RAID 0, 1, 5, 10	Form Factor	1U Rackmount
LAN	2x Gigabit Ethernet LAN ports, 1x RJ45 Dedicated IPMI LAN port	Width: 17.2" (437mm), Height: 1.7" (43mm), Depth: 19.8" (503mm)	
Add-on Options		<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit</p> <p>www.tyronesystems.com</p>	
Raid	Optional		
Optical Drive	Optional		