

Tyrone Camarero Specifications

Camarero SS400TR-14T

Tyrone

Key features

Storage HN, VM, Hosting, Mainstream, Small file server, Entry Caching Appliance

- Single socket H4 (LGA 1151) supports Intel® Xeon® processor E3-1200 v6/v5, Intel® 7th/6th Gen. Core™ i3 series, Intel® Celeron® and Intel® Pentium®
- Intel® C236 chipset
- 4 Hot-swap 3.5" SATA3 drive bays
- Up to 64GB Unbuffered ECC UDIMM DDR4 2400MHz; 4 DIMM slots
- 1 PCI-E 3.0 x8 AOC slot
- 2x 10GBase-T ports with Intel® X550
- Integrated IPMI 2.0 and KVM with Dedicated LAN
- I/O ports: 1x VGA, 2x COM, 2x USB 3.0 (front/rear), USB 2.0
- 350W High-efficiency Power Supply Platinum Level Certified



Processor/Cache

Processor	Single socket H4 (LGA 1151) supports Intel® Xeon® processor E3-1200 v6/v5, Intel® 7th/6th Gen. Core™ i3 series, Intel® Celeron® and Intel® Pentium®
-----------	---

Chipset

Chipset	Intel® C236 chipset
---------	---------------------

System Memory

Memory Capacity	Up to 64GB Unbuffered ECC UDIMM DDR4 2400MHz; 4 DIMM slots
-----------------	--

Expansion Slots

PCI Express	1x PCI-E 3.0 x8 AOC slot
-------------	--------------------------

Integrated On-Board

SATA	SATA3 (6Gbps) via C236 controller RAID 0, 1, 5, 10 support
LAN	2x RJ45 10GBase-T LAN ports, 1x RJ45 Dedicated IPMI LAN port

Add-on Options

Raid Card	Optional
Optical Drive	Optional

Front Panel

LED	Power LED, Hard drive activity LED, 2x Network activity LEDs, System Overheat LED
Buttons	Power On/Off button, System Reset button

Drive Bays

HDD Bays	4 Hot-swap 3.5" SATA3 drive bays
Peripheral Drives	2 Fixed 2.5" internal drives

Power Supply

350W High-efficiency Power Supply Platinum Level Certified

Cooling System

4x 40x28mm 4-pin PWM Cooling Fans

Form Factor

Form Factor	1U Rackmount
Width:	17.2" (437mm),
Height:	1.7" (43mm),
Depth:	19.8" (503mm)

Email : info@tyronesystems.com

For more/current product information, visit
www.tyronesystems.com