Tyrone Camarero Specifications

Camarero SS400Ti-45L Key features

Workstation

- Single socket H4 (LGA 1151) supports Intel® Xeon® processor E3-1200 v5/v6,Intel® 6th/7th Gen.
 Core™ i7/i5/i3 series, Intel® Celeron® and Intel® Pentium®
- Intel® C236 chipset
- Up to 64GB Unbuffered ECC/non-ECC UDIMM DDR4 2400MHz; 4 DIMM slots
- 2 PCI-E 3.0 x16 (run at 16/NA or 8/8), 2 PCI-E 3.0 x1, and 2 5V PCI 32-bit slots
- Single GbE LAN with Intel® i210-AT (Share with IPMI); single GbE LAN with Intel® i219LM
- 8 SATA3 (6Gbps) via C236; RAID 0, 1, 5, 10 + 1 PCI-E M.2 (support PCI-E x4 only, 2242/2260/2280)
- I/O: 1 VGA, 2 COM, TPM header
- 6 USB 3.0 (2 rear + 4 via header(s)) 6 USB 2.0 (2 rear + 4 via header(s)) 2 USB 3.1 (10Gbps, rear)
- External:5.25" x 4, 3.5" x 1,Internal: 3.5" or 2.5" x 5
- Front: 120 x 25 mm x1 PWM Fan, Rear: 120 x 25 mm x1 PWM Fan
- 500/1200 Single Power Supply, 80 Plus Platinum





Processor/Cache

Processor Single socket H4 (LGA 1151) supports

Intel® Xeon® processor E3-1200 v5/v6,Intel® 6th/7th Gen. Core™ i7/i5/i3 series, Intel® Celeron® and

Intel® Pentium®

Chipset

Chipset Intel® C236 chipset

System Memory

Memory Capacity Up to 64GB Unbuffered ECC/non-ECC

UDIMM, DDR4-2400MHz, in 4 DIMM slots, 4x 288-pin DDR4 DIMM slots, Up to 64GB DDR4 ECC UDIMM

Expansion Slots

PCI-Express 2 PCI-E 3.0 x16 (run at 16/NA or 8/8),

2 PCI-E 3.0 x1, and 2 5V PCI 32-bit slots

Integrated On-Board

SATA Intel® C236 controller for 8 SATA3

(6 Gbps) ports; RAID 0,1,5,10

LAN Single GbE LAN with Intel® i210-AT

(Share with IPMI); single GbE LAN with

Intel® i219LM

Add-on Options

Raid Card Optional

Optical Drive Optional

Front Panel

Front Panel Front Control Panel Power Switch,

System Reset

Buttons Power On/Off button

Drive Bays

Drive Bays External:5.25" x 4, 3.5" x 1,

Internal: 3.5" or 2.5" x 5

Peripheral Drives Optional

Power Supply

500/1200 Single Power Supply, 80 Plus Platinum

Cooling System

Front: 120 x 25 mm x1 PWM Fan, Rear: 120 x 25

mm x1 PWM Fan

Form Factor

Form Factor : Tower/Convertable/5U Rackmount

Dimensions : 560 x 200 x 430 mm (22" x 7.9" x 16.9")

Email: info@tyronesystems.com
For more/current product information, visit

www.tyronesystems.com

O Intel, the Intel logo, the Intel Inside logo, Xeon, and Intel Xeon Phi are trademarks of intel Corporation in the U.5 and/Or other Countries

Specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks. All other brands and names are the property of their respective owners