

Tyrone Camarero Specifications

Tyrone[®]

Camarero SS4C0TR-34

Key features

- Single socket H4 (LGA 1151) supports, Intel® Xeon® processor E3-1200 v5, Intel® 6th Gen. Core™ i3 series, Intel® Celeron® and Intel® Pentium®
- Intel® C236 chipset
- Up to 64GB Unbuffered ECC UDIMM DDR4 2133MHz; 4x DIMM slots
- 1 PCI-E 3.0 x8 (in x16), 1 PCI-E 3.0 x8, 1 PCI-E 3.0 x4 (in x8)
- Dual GbE LAN with Intel® i210-AT
- 8x SATA3 (6Gbps) via C236; RAID 0, 1, 5, 10
- I/O: 1x VGA, 2x COM, 2x SuperDOM, and TPM header
- 5x USB 3.0 (2 rear + 2 via header + 1 Type A), 6x USB 2.0 (2 rear + 4 via headers)
- Integrated IPMI 2.0 and KVM with Dedicated LAN
- 2x 5.25" external drive bays, 4x 3.5" internal drive bays, 1x 3.5" external drive bay (OEM)
- 300W High-efficiency Power Supply



Processor/Cache		Front Panel	
Processor	Single socket H4 (LGA 1151) supports Intel® Xeon® processor E3-1200 v5, Intel® 6th Gen. Core™ i3 series, Intel® Celeron® and Intel® Pentium®	Led's	Power LED, Hard drive activity LED, Network activity LED, System Overheat LED
Chipset	Intel® C236 chipset	Buttons	Power On/Off button,
System Memory		Drive Bays	
Memory Capacity	64GB Unbuffered ECC UDIMM, DDR4-2133MHz, in 4 DIMM slots	HDD bays	4x 3.5" tool-less HDD trays, SAS or enterprise SATA HDD only recommended, 2x 5.25" external drive bays, 1x 3.5" external drive bay (OEM option)
Expansion Slots		Power Supply	
PCI Express	1 PCI-E 3.0 x8 (in x16), 1 PCI-E 3.0 x8, 1 PCI-E 3.0 x4 (in x8)	300W High-efficiency Power Supply	
Integrated On-Board		Cooling System	
SATA	Intel® C236 controller for 8 SATA3 (6Gbps) ports; RAID 0, 1, 5, 10	1x 9cm (rear) PWM fan w/ tool-less design. 1x 8cm (front) cooling fan (optional). Optimized Cooling Technology at 25dB Whisper-Quiet Operation	
Add-on Options		Form Factor	
Raid Card	Optional	Form Factor	Mid Tower
Optical Drive	None	Width:	7.25" (184 mm),
		Height:	14.25" (362 mm),
		Depth:	16.75" (425 mm)
		<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit</p> <p>www.tyronesystems.com</p>	