

Tyrone Camarero Specifications

Tyrone

Camarero SSI200F0R-55

Key Feature

- "12th/13th Gen Intel® Core™ i3/i5/i7/i9 Processors Single Socket LGA-1700 (Socket V0) supported, CPU TDF supports Up to 150W TDP"
- Single LAN with Intel® Ethernet i225V, Single LAN with Intel® PHY I219LM LAN controller for AMT/vPro
- Intel® W680
- 2 PCI-E 5.0 x16 slots (16/NA or 8/8)2 PCI-E 3.0 x4, 1 - 5V PCI 32bit, M.2 Interface: 3 PCI-E 4.0 x4, RAID 0,1,5, M.2 Form Factor: 2280, M.2 Key: M-Key
- 128GB Unbuffered ECC/non-ECC UDIMM, DDR5-4400MHz, in 4 DIMM slots
- Intel® W680 controller for 8 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 1 DP 1.4a port, 1 HDMI 2.1 port, 1 DVI - D port
- Supports PS2, ATX12V 600W or 2U 1 + 1 x 80 Plus Platinum 1200W CRPS
- External 5.25" x 4, 3.5" x 1, Internal 2.5"/3.5" x 5
- Front: 120 x 25 mm x1 PWM Fan,Rear: 120 x 25 mm x1 PWM Fan Optional : Liquid Cooling Module w/ a 3-pin Pump Connector
- 550/1200W Redundant Power Supply , Optional : 500/1200W Single Power Supply
- Optional : Dedicated LAN for IPMI



Processor/Cache		Front Panel	
Processor	"12th/13th Gen Intel® Core™ i3/i5/i7/i9 Processors Single Socket LGA-1700 (Socket V0) supported, CPU TDP supports Up to 150W TDP"	LEDs	1 RJ45 Gigabit Ethernet LAN ports, 1 RJ45 2.5 Gigabit Ethernet LAN port
System Memory		Buttons	Power On/Off button, System Reset
Memory	128GB Unbuffered ECC/non-ECC UDIMM, DDR5-4400MHz, in 4 DIMM slots	Drive bays	
Chipset		Drive Bays	8x 3.5"/2.5" hot-swap SAS drive bay with SES3
Chipset	Intel® W680	Peripheral Drives	3x standard 5.25" drive bay
Expansion Slot		Power Supply	
PCI-Express	"2 PCI-E 5.0 x16 slots (16/NA or 8/8)2 PCI-E 3.0 x4, 1 - 5V PCI 32bit, M.2 Interface: 3 PCI-E 4.0 x4, RAID 0,1,5, M.2 Form Factor: 2280M.2 Key:	Power Supply	1200W (1 + 1) Redundant Titanium Level Certified High-Efficiency Power Supply
Integrated On-Board		Cooling System	
SATA	Intel® W680 controller for 8 SATA3 (6 Gbps) ports; RAID 0,1,5,10	Fans	2x 80mm PWM Rear Chassis Fans (9.4k RPM), 3x 80mm high-performance fan(s) (9.4k RPM)
LAN	1 RJ45 Gigabit Ethernet LAN ports, 1 RJ45 2.5 Gigabit Ethernet LAN port	Form Factor	
Add-on Options		Form Factor	4U Tower Dimensions: Height :17.8" (452 mm), Width : 17.8" (452 mm), Depth : 25.5" (647 mm)
Raid Card	Optional	Email : Info@tyronesystems.com	
Optical Drive	Optional	For more/current product information, Visit www.tyronesystems.com	