

Tyrone Camarero Specifications

Tyrone

Camarero TDI10C3R-48

Key Feature

- Dual Socket Intel Ice Lake SP CPU, 3rd Gen Intel Xeon Scalable Processor, LGA4189
- (8)+(8) DIMM slots DDR4 ECC RDIMM/RDIMM 3DS/LRDIMM/LRDIMM 3DS 3200, Up to 2,048GB RDIMM/ 4,096GB LRDIMM/ 4,096GB RDIMM 3DS/LRDIMM 3DS *Follow latest Intel DDR4 Memory POR
- Intel C621A chipset
- 3 PCIe Gen. 4x16 + 2 PCIe Gen.4x8 slots
- 2 PCIe x8 SlimSASconnectors (NVMe)
- 2 NVMe 22110 / 2280 M.2 slots
- 2 1000Base-T LAN + 1 dedicate 1000Base-T IPMI ports
- AST2600 BMC with IPMI 2.0 & Redfish support
- Whisper-Quiet (<27dB)
- 8x 3.5"/2.5" SAS3/SATA3 Backplane for Hot-Swappable Drives, 3x standard 5.25" Peripheral bays
- 3x Middle 8cm (9400 rpm) PWM Fans & 2x 8cm (9400 rpm) PWM Fans
- 900W/1200W Redundant Power Supply,
Optional : 900W/1200W Single Power Supply.



Processor/Cache	
Processor	Dual Socket Intel Ice Lake SP CPU, 3rd Gen Intel Xeon Scalable Processor, LGA4189
System Memory	
Memory	(8)+(8) DIMM slots DDR4 ECC RDIMM/RDIMM 3DS/LRDIMM/LRDIMM 3DS 3200, Up to 2,048GB RDIMM/ 4,096GB LRDIMM/ 4,096GB RDIMM 3DS/LRDIMM 3DS
Chipset	
Chipset	Intel C621A chipset
Expansion Slot	
PCI-Express	3 PCIe Gen. 4x16 + 2 PCIe Gen.4x8 slots
Integrated On-Board	
SATA	(3) Mini-SAS HD from PCH SATA-III
LAN	Intel I210-AT
IPMI	IPMI 2.0 compliant baseboard management controller (BMC) / 10/100/1000 Mb/s MAC interface
Add-on Options	
Raid Card	Optional
Optical Drive	Optional

Drive bays	
Drive Bays	8x 3.5"/2.5" SAS/SATA Backplane for Hot-Swappable Drives
Peripheral drives	2x standard 5.25" drive bay,90 degree rotatable drive cage
Power Supply	
Power Supply	900W/1200W Redundant Power Supply Optional : 900W/1200W Single Power Supply.
Cooling System	
Fans	3x Middle 8cm (9400 rpm) PWM Fans & 2x 8cm (9400 rpm) PWM Fans
Form Factor	
Form Factor	4U Rackmount Dimensions: Height -17.8" (452 mm), Width -7" (178 mm), Depth -25.5" (647 mm)
<p>Email : Info@tyronesystems.com</p> <p>For more/current product information, Visit www.tyronesystems.com</p>	

• Intel, the Intel logo,the Intel Inside logo,Xeon,and Intel Xeon Phi are trademarks of Intel Corporation in the U.S and/Or other Countries
• Specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks. All other brands and names are the properties of their respective owners