

Tyrone Camarero Specifications

Tyrone[®]

Camarero TSS300T6R-14R

Key features

- Single socket H3 (LGA 1150) supports Intel® Xeon® E3-1200 v3, 4th gen. Core i3, Pentium, Celeron processors
- Intel® C222 Express PCH
- Four memory sockets, Supports up to 32 GB DDR3 ECC 1600MHz Un- buffered memory
- Dual Gigabit Ethernet LAN ports (1x Intel® i217LM & 1x Intel® i210AT)
- 2x SATA (6Gbps), 4x SATA (3Gbps)
- 1x PCI-E 3.0 x8 (in x16), 1x PCI-E 3.0 x8, and 1x PCI-E 2.0 x4 (in x8) slots
- 2x USB 3.0 (1 Type-A + 1 via header) 6x USB 2.0 (4 rear + 2 via header)
- Integrated IPMI 2.0 with KVM and Dedicated LAN
- SATA DOM power connector support
- 4x 3.5" hot-plug SATA HDD Bays
- VGA D-sub connector, TPM header
- 400W single PSU 80+ ,500W single PSU 80+ (Bronze) ,500W 1+1 hot-swap redundant 80+



Processor/Cache		Front Panel :	
Processor	Single Socket Intel® Xeon® E3-1200 v3, 4th gen. Core i3, Pentium, Celeron processors	LED Indicators	Power LED, Hard drive activity LED, Network activity LED
		Switches	Power on/off, System Reset
Chipset		Drive bays	
	Intel® C222 Express PCH	HDD (Internal)	2 x 2.5"
		(External)	4 x 3.5" hot swap & 1 x Slim DVD-ROM
System Memory		Power Supply	
Memory Capacity	Four memory sockets, Supports up to 32 GB DDR3 ECC 1600MHz Un- buffered memory		400W single PSU 80+ ,500W single PSU 80+ (Bronze) ,500W 1+1 hot-swap redundant 80+
Expansion Slots		Cooling System	
PCI-Express	1x PCI-E 3.0 x8 (in x16), 1x PCI-E 3.0 x8, and 1x PCI-E 2.0 x4 (in x8) slots		5 x easy swap middle fans for superior cooling
Integrated On-Board		Form Factor	
SATA	SATA3 (6Gbps) w/ RAID 0, 1, SATA2 (3Gbps) w/ RAID 0, 1, 5, 10		1U Rackmount with Rails,
LAN	2x Gigabit Ethernet LAN ports, 1x RJ45 Dedicated IPMI LAN port		Width- 482.6 mm, Height- 44.4 mm , Depth – 660 mm
Add-on Options		Email : info@tyronesystems.com For more/current product information, visit www.tyronesystems.com	
Optical	Optional		