

# Tyrone Camarero Specifications

# Tyrone

## Camarero AD400TE1-216R

### Key features

- EATX Server Board with dual Xeon Scalable processors
- Intel C621
- DDR4 2666 MHz RDIMM up to 768 GB (24 DIMMs)
- 5 PCIe x16 (Gen3) and one PCIe x8 (Gen3) for three double-deck cards
- LAN1: Intel I210AT , LAN2: Intel I210AT, 10/100/1000 Mbps, 2 x RJ-45
- 10 SATA3 and six USB3.0 ports
- One M.2 2280 (SATA / PCIe compatible)
- 0 ~ 40 °C ambient operation temperature range
- 16 x 3.5" hot-swap SAS3/SATA drive bay, optional 2 x 2.5" hot-swap SAS/SATA drive bay
- 4 x 80x38mm hot-swap cooling fan(s)
- 800W/1000W/1600W Redundant Power Supply



### Processor/Cache

Processor EATX Server Board with dual Xeon Scalable processors

### Chipset

Chipset Intel C621

### System Memory

Memory Capacity DDR4 2666 MHz RDIMM up to 768 GB (24 DIMMs)

### Expansion Slots

PCI-Express 5 PCIe x16 (Gen3) and one PCIe x8 (Gen3) for three double-deck cards

### Integrated On-Board

SATA 10 x SATAIII (RAID 0,1,5,10)

LAN LAN1: Intel I210AT,LAN2: Intel I210AT

### Add-on Options

Raid Card Optional

Optical Drive None

### Front Panel

LED 2 Network Activity LEDs,HDD Fail LED, Power Status LED,Power Fail LED,System Information LED

Buttons Power On/Off button,System Reset Button

### Drive Bays

HDD Bays 16 x 3.5" hot-swap SAS3/SATA drive bay, Optional 2 x 2.5" hot-swap SAS/SATA drive bay

### Power Supply

800W/1000W/1600W Redundant Power Supply

### Cooling System

Fans:4 x 80x38mm hot-swap cooling fan(s)

### Form Factor

Form Factor : 2U Rackmount  
Height : 3.5" (89 mm)  
Width : 17.2" (437 mm)  
Depth : 27.75" (705 mm)

Email : [info@tyronesystems.com](mailto:info@tyronesystems.com)

For more/current product information, visit

[www.tyronesystems.com](http://www.tyronesystems.com)