

Tyrone Camarero Specifications

Tyrone

Camarero AD400TR-28

Key features

- EATX Server Board with dual Xeon Scalable processors
- Intel C621
- DDR4 2666 MHz RDIMM up to 768 GB (24 DIMMs)
- 5 PCIe x16 (Gen3) and one PCIe x8 (Gen3) for three double-deck cards
- LAN1: Intel I210AT , LAN2: Intel I210AT, 10/100/1000 Mbps, 2 x RJ-45
- 10 SATA3 and six USB3.0 ports
- One M.2 2280 (SATA / PCIe compatible)
- 0 ~ 40 °C ambient operation temperature range
- 8 x 3.5" hot-swap SAS3/SATA drive bay, 2 x 3.5" fixed drive bay
- 3 x 8cm (7000 RPM) hot-swap PWM cooling fan(s)
- 600W platinum efficiency multiple output power supply w/PMBus



Processor/Cache

Processor EATX Server Board with dual Xeon Scalable processors

Chipset

Chipset Intel C621

System Memory

Memory Capacity DDR4 2666 MHz RDIMM up to 768 GB (24 DIMMs)

Expansion Slots

PCI-Express 5 PCIe x16 (Gen3) and one PCIe x8 (Gen3) for three double-deck cards

Integrated On-Board

SATA 10 x SATAIII (RAID 0,1,5,10)

LAN Intel I210AT; LAN2: Intel I210AT

Add-on Options

Raid Card Optional

Optical Drive Optional

Front Panel

Led's 2 Network Activity LEDs,HDD activity LED, Power Status LED,Power Fail LED,System Information LED

Buttons Power On/Off button,System Reset Button

Drive Bays

Drive Bays 8 x 3.5" hot-swap SAS3/SATA drive bay, 2 x 3.5" fixed drive bay

Peripheral Drives Optional 1 x slim DVD-ROM drive bay, Optional 2 x USB 2.0 ports,Optional 1 x COM port tray,Optional 2 x USB 3.0 ports

Power Supply

600W platinum efficiency multiple output power supply w/PMBus

Cooling System

3 x 8cm (7000 RPM) hot-swap PWM cooling fan(s)

Form Factor

Form Factor : 2U Rackmount

Height : 3.5" (89 mm)

Width : 17.2" (437 mm)

Depth : 25.5" (647 mm)

Email : info@tyronesystems.com

For more/current product information, visit

www.tyronesystems.com