

# Tyrone Camarero Specifications

**Tyrone**<sup>®</sup>

Camarero DS40012E1-224RL

## Key features

- **Corporate Database, Database Processing & Storage, Enterprise Server, HPC, Data Center. iSCSI SAN**
- 2nd Generation Intel® Xeon® Scalable Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors., Dual Socket P (LGA 3647) supported, CPU TDP support 205W, 3 UPI up to 10.4 GT/s
- Intel® C621 chipset
- Up to 6TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 6TB 3DS ECC LRDIMM, DDR4-2933MHz, in 24 DIMM slots; Up to 6TB Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only);
- 2 PCI-E 3.0 x16 slots, 1 PCI-E 3.0 x8 slot, 1 SIOM card support (flexible networking)  
Note: must bundle with Network card
- 24 Hot-swap 3.5" SAS3/SATA3 drive bays; 2 hot-swap 2.5" drive bays (rear)
- Broadcom 3008 SAS3, IT mode
- 2x 10GBase-T LAN ports with Intel X722 + PHY Intel X557
- Server remote management: IPMI 2.0 / KVM over LAN / Media over LAN
- 1600W Redundant Power Supplies Titanium Level (96%)



Processor/Cache		Front Panel	
Processor	2nd Generation Intel® Xeon® Scalable Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors., Dual Socket P (LGA 3647) supported, CPU TDP support 205W, 3 UPI up to 10.4 GT/s	Led's	Power status LED, Hard drive activity LED, Network activity LEDs, System Overheat LED, Power fail LED
Chipset	Intel® C621 chipset	Buttons	Power On/Off button, System Reset button
System Memory		Drive Bays	
Memory Capacity	Up to 6TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 6TB 3DS ECC LRDIMM, DDR4-2933MHz, in 24 DIMM slots; Up to 6TB Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only).	HDD bays	24 Hot-swap 3.5" SAS3/SATA3 drive bays, 2 Hot-swap 2.5" SATA3 drive bays (rear)
Expansion Slots	2 PCI-E 3.0 x16 slots, 1 PCI-E 3.0 x8 slot, 1 SIOM card support	Optional	2 Optional Onboard NVMe M.2
Integrated On-Board		Power Supply	
SAS	SAS3 (12Gbps) via Broadcom 3008; IT Mode	1600W Redundant Power Supplies Titanium Level (96%)	
SATA	SATA3 (6Gbps); RAID 0, 1, 5, 10	Cooling System	
LAN	2 RJ45 10GBase-T LAN ports, 1 RJ45 Dedicated IPMI LAN port	5x 8cm high-performance PWM fans	
Add-on Options		Form Factor	
Optical Drive	None	Form Factor	2U Rackmount
		Width	17.2" (437mm) ,
		Height	3.5" (89mm) ,
		Depth	34" (863mm)

**Email : [info@tyronesystems.com](mailto:info@tyronesystems.com)**

**For more/current product information, visit**

**[www.tyronesystems.com](http://www.tyronesystems.com)**