

Tyrone Camarero Specifications

Tyrone®

Camarero DS4007E1-212RT

Key features

- Corporate Database, Database Processing & Storage, Enterprise Server, HPC, Data Center. iSCSI SAN
- 2nd Generation Intel® Xeon® Scalable Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors. Dual Socket P (LGA 3647) supported, CPU TDP support 205W, 3 UPI up to 10.4 GT/s
- Intel® C622 chipset
- Up to 4TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 4TB 3DS ECC LRDIMM, DDR4-2933MHz, in 16 DIMM slots; Up to 2TB Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only)
- 3 PCI-E 3.0 x16, 4 PCI-E 3.0 x8, (slot 2 & 3 occupied by controller and JBOD expansion port)
- 12 Hot-swap 3.5" SAS3/SATA3 direct attached drive bays
- Broadcom 3108 SAS3 AOC
- 2x 10GBase-T LAN ports with Intel X722 + PHY Intel X557
- Server remote management: IPMI 2.0 / KVM over LAN / Media over LAN
- 3 Hot-swap 8cm redundant PWM fans
- 1200W Redundant Power Supplies Titanium Level (96%)



Processor/Cache		Front Panel	
Processor	2nd Generation Intel® Xeon® Scalable Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors. Dual Socket P (LGA 3647) supported, CPU TDP support 205W, 3 UPI up to 10.4 GT/s	Led's	Power status LED, Hard drive activity LED, Network activity LEDs, System Overheat LED, Power fail LED
Chipset	Intel® C622 chipset	Buttons	Power On/Off button, System Reset button
System Memory		Drive Bays	
Memory Capacity	Up to 4TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 4TB 3DS ECC LRDIMM, DDR4-2933MHz, in 16 DIMM slots; Up to 2TB Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only)	HDD bays	12 Hot-swap 3.5" SAS3/SATA3 drive bays, 2 Optional Onboard NVMe M.2
Expansion Slots		Power Supply	
PCI-Express	3 PCI-E 3.0 x16 slot, 4 PCI-E 3.0 x8 slots, Slot 2 & 3 occupied by controller and JBOD expansion port	1200W Redundant Power Supplies Titanium Level (96%)	
Integrated On-Board		Cooling System	
SAS	SAS3 (12Gbps) via Broadcom 3108 AOC; HW RAID, RAID 0, 1, 5, 6, 10, 50, 60	3 Hot-swap 8cm redundant PWM cooling fans	
SATA	SATA3 (6Gbps); RAID 0, 1, 5, 10	Form Factor	
LAN	2 RJ45 10GBase-T LAN ports, 1 RJ45 Dedicated IPMI LAN port	Form Factor	2U Rackmount
Add-on Options		Height	: 3.5" (89mm),
Optical Drive	None	Width	: 17.2" (437mm),
		Depth	: 24.8" (630mm)
		<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit</p> <p>www.tyronesystems.com</p>	

Intel, the Intel logo, the Intel Inside logo, Xeon, and Intel Xeon Phi are trademarks of Intel Corporation in the U.S. and/or other countries. Specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks. All other brands and names are the property of their respective owners.