Tyrone Camarero Specifications

Camarero DS4007E1-460R

Key features

- Corporate Database, Database Processing & Storage, Enterprise Server, HPC, Data Center. iSCSI SAN
- 2nd Generation Intel® Xeon® Scalable Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors., Dual Socket P (LGA 3647) supported, CPU TDP support 205W, 3 UPI up to 10.4 GT/s
- . Intel® C621 chipset
- Up to 6TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 6TB 3DS ECC LRDIMM, DDR4-2933MHz, in 24 DIMM slots;Up to 6TB Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only).
- 2 PCI-E 3.0 x16, 1 PCI-E 3.0 x8, 1 SIOM, card support (flexible networking), Note: must bundle with Network card
- 60 Hot-swap 3.5" SAS3/SATA3 drive bays with SES3; 2 rear Hot-swap 2.5"drive bays
- Broadcom 3108 SAS3, HW RAID
- · Server remote management: IPMI 2.0/ KVM over LAN / Media over LAN
- . 5 Hot-swap 8cm rear exhaust PWM fans
- 2000W Redundant Power Supplies Titanium Level (96%)





Processor/Cache

Processor 2nd Generation Intel® Xeon® Scalable

Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors., Dual Socket P (LGA 3647) supported, CPU TDP support 205W, 3 UPI up to 10.4 GT/s

Chipset

Chipset Intel® C621 chipset

System Memory

Memory Capacity Up to 6TB 3DS ECC RDIMM,

DDR4-2933MHz; Up to 6TB 3DS ECC LRDIMM, DDR4-2933MHz, in 24 DIMM slots;Up to 6TB Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only).

VI-8000-000

Expansion Slots

PCI-Express

2 PCI-E 3.0 x16 slots,1 PCI-E 3.0 x8 slot,

1 SIOM card support,

(must bundle with network card)

Integrated On-Board

SAS SAS3 (12Gbps) via Broadcom 3108 AOC;

HW RAID, RAID 0, 1, 5, 6, 10, 50, 60

SATA SATA3 (6Gbps); RAID 0, 1, 5, 10

LAN 1 RJ45 Dedicated IPMI LAN port

Add-on Options

Optical Drive None

Front Panel

Led's Power status LED, Hard drive activity LED,

Network activity LEDs, System Overheat

LED.Power fail LED

Buttons Power On/Off button, System Reset button

Drive Bays

HDD bays 60 Hot-swap 3.5" SAS3/SATA3 drive bays,

2 Rear Hot-swap 2.5" SATA drive bays

Power Supply

2000W Redundant Power Supplies Titanium Level (96%)

Cooling System

5 Hot-swap 8cm rear exhaust PWM fans

Form Factor

Form Factor 4U Rackmount

Height : 7" (178mm), Width : 17.2" (437mm), Depth : 30.2" (767mm)

Email: info@tyronesystems.com

For more/current product information, visit

www.tyronesystems.com