Tyrone Camarero Specifications

Camarero DS400TGQN-12RT

Key features

- Supports up to 4 GPUs in 1U, Support Active/Passive GPUs, GPU health monitoring with Fan speed control
- 2nd Generation Intel® Xeon® Scalable Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors. Dual Socket P (LGA 3647) supported, CPU TDP support 205W, 3 UPI up to 10.4 GT/s
- Intel® C621 chipset
- Up to 3TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 3TB 3DS ECC LRDIMM, DDR4-2933MHz, in 12 DIMM slots;Up to 2TB Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only)
- 4 PCI-E 3.0 x16 (FHFL), 1 PCI-E 3.0 x16 (LP) and 1 PCI-E 3.0 x8 (LP)
- 2 Hot-swap 2.5" SAS/SATA/NVMe drive bays, 2 Internal 2.5" drive bays
- 2x 10GBase-T LAN ports via Intel X540
- 9 Heavy duty 4cm counter-rotating fans with air shroud & optimal fan speed control
- 2000W Redundant Power Supplies Titanium Level (96%)









Processor/Cache

2nd Generation Intel® Xeon® Scalable Processor

Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors. Dual Socket P (LGA 3647) supported, CPU TDP support

205W, 3 UPI up to 10.4 GT/s

Chipset

Chipset Intel® C621 chipset

System Memory

Memory Capacity Up to 3TB 3DS ECC RDIMM, DDR4-

> 2933MHz; Up to 3TB 3DS ECC LRDIMM, DDR4-2933MHz, in 12 DIMM slots;Up to 2TB Intel® Optane™ DC Persistent

Memory in memory mode (Cascade Lake only)

Expansion Slots

PCI-Express 4 PCI-E 3.0 x16 (FHFL) slots,

> 1 PCI-E 3.0 x16 (LP) slot, 1 PCI-E 3.0 x8 (LP) slot

Integrated On-Board

SATA 4 SATA3 (6Gbps) with RAID 0, 1, 5, 10

LAN 2 RJ45 10GBase-T ports,

1 RJ45 Dedicated IPMI LAN port

Add-on Options

Raid Card Optional Optical Drive None

Front Panel

LED Indicators Power LED, Hard drive activity LED,

Network activity LEDs, System Overheat

LED / Fan fail LED / UID LED

Power On/Off button, UID button **Buttons**

Drive Bays

HDD Bays

2 Hot-swap 2.5"" U.2 NVMe drive bays, Fixed: 2 Internal 2.5" SATA

drive bays

M.2: Support 1x M.2 2242/2260/2280,

Support M.2 SATA and NVMe

Power Supply

2000W Redundant Power Supplies Titanium Level (96%)

Cooling System

9 Heavy duty 4cm counter-rotating fans with air shroud & optimal fan speed control

Form Factor

1U Rackmount Form Factor

Height : 1.7° (43mm), Width 17.2" (437mm)

35.2" (894mm) 39.3" (997mm) with rails Depth

Email: info@tyronesystems.com

For more/current product information, visit www.tyronesystems.com

Intel, the Intel logo, the Intel Inside logo, Xeon, and Intel Xeon Phi are trademarks of Intel Corporation in the U.S and/Or other Countries

Specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks. All other brands and names are the property of their respective owners