Tyrone Camarero Specifications

Tyrone

Camarero DS400TR-18RL

Key features

- Data Center Optimized, Web Server, Enterprise Server, Managed Hosting, Short Depth
- 2nd Generation Intel® Xeon® Scalable Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors.Dual Socket P (LGA 3647) supported, CPU TDP support Up to 140W, 2 UPI up to 10.4 GT/s
- Intel ®C621 chipset
- Up to 2TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 2TB 3DS ECC LRDIMM, DDR4-2933MHz, in 8 DIMM slots
- 1 PCI-E 3.0 x8 (FHHL) slot
- 8 Hot-swap 2.5" SATA3 drive bays, 1 Slim DVD-ROM drive (optional), Optional PCIe/SATA M.2 drive
- 2 1GbE LAN ports via Marvell 88E1512
- . IPMI 2.0 + KVM with Dedicated LAN
- 1 VGA, 2 USB 2.0 (rear)
- 2 SuperDOM (Disk on Module) ports; 1 PCIe/SATA M.2 drive connector
- 800W Redundant Power Supplies Platinum Level







Processor/Cache

Processor

2nd Generation Intel® Xeon® Scalable
Processors (Cascade Lake-SP), Intel®
Xeon® Scalable Processors.Dual Socket P

(LGA 3647) supported, CPU TDP support Up to 140W, 2 UPI up to 10.4 GT/s

Chipset

Chipset Intel *C621 chipset

System Memory

Memory Capacity Up to 2TB 3DS ECC RDIMM, DDR4-2933

MHz; Up to 2TB 3DS ECC LRDIMM, DDR4-

2933MHz, in 8 DIMM slots

Expansion Slots

PCI-Express 1 PCI-E 3.0 x8 (FHHL) slot

Integrated On-Board

SATA SATA3 (6Gbps); RAID 0, 1, 5, 10

LAN 2 RJ45 Gigabit Ethernet LAN ports,

1 RJ45 Dedicated IPMI LAN port

Add-on Options

Raid Card Optional
Optical Drive Optional

Front Panel

LED Indicators Power status LED, HDD activity LED,

Network activity LEDs,

Universal Information (UID) LED

Buttons Power On/Off button, System Reset button

Drive Bays

HDD Bays 8 Hot-swap 2.5" SATA3 drive bays

Peripheral Bays Slim DVD-ROM drive (optional),

PCIe/SATA M.2 drive (optional)

Power Supply

800W Redundant Power Supplies Platinum Level

Cooling System

4x 4cm 22.5K RPM middle cooling fans

Form Factor

Form Factor 1U Rackmount

Height : 1.7* (43mm), Width : 17.2" (437mm), Depth : 19.98" (508mm)

Email: info@tyronesystems.com

For more/current product information, visit

www.tyronesystems.com

o Intel, the Intel logo, the Intel Inside logo, Xeon, and Intel Xeon Phi are trademarks of Intel Corporation in the U.S and/Or other Countries

O Specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks. All other brands and names are the property of their respective owners