

Tyrone Camarero Specifications

Tyrone[®]

Camarero DS400TU-224R25M

Key features

- **Virtualization,Hyperconverge Storage,Cloud Computing,High End Enterprise Server**
- 2nd Generation Intel® Xeon® Scalable Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors., Dual Socket P (LGA 3647) supported, CPU TDP support 205W, 2 UPI up to 10.4 GT/s
- Intel® C621 chipset
- Up to 6TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 6TB 3DS ECC LRDIMM, DDR4-2933MHz, in 24 DIMM slots;Up to 6TB Intel® Optane™ DC Persistent Memory in memory mode.
- 1 PCI-E 3.0 x16 slot (FH, 10.5" L),5 PCI-E 3.0 x8 slots (FH, 10.5" L),1 PCI-E 3.0 x8 slot (LP), 1 PCI-E 3.0 x8 slot (internal LP)
- 2 25GbE SFP28 Ethernet ports
- 24 Hot-swap 2.5" drive bays; 14 SATA3,(optional 20 SAS3 + 4 NVMe/SAS3),Optional 2 hot-swap 2.5" rear drive bays for SSDs;Optional M.2 NVMe and SATA3 ports
- 4 Heavy duty 8cm PWM fans
- 1000W Redundant Power Supplies Titanium Level (96%)



Processor/Cache		Front Panel	
Processor	2nd Generation Intel® Xeon® Scalable Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors., Dual Socket P (LGA 3647) supported, CPU TDP support 205W, 2 UPI up to 10.4 GT/s	Led's	Power status LED,HDD activity LED, Network activity LEDs System information (overheat/UID) LED
Chipset	Intel® C621 chipset	Buttons	Power On/Off button,System Reset button
System Memory		Drive Bays	
Memory Capacity	Up to 6TB 3DS ECC RDIMM,DDR4-2933MHz; Up to 6TB 3DS ECC LRDIMM, DDR4-2933MHz, in 24 DIMM slots;Up to 6TB Intel® Optane™ DC Persistent Memory in memory mode.	HDD Bays	24 Hot-swap 2.5" drive bays;14 SATA3 (optional 20 SAS3 + 4 NVMe/SAS3)
Expansion Slots		M.2	M.2:1 M.2 PCI-E 3.0 x4 M-Key NVMe and 1 M.2 M-Key SATA3 via optional riser card RSC-UMR-8, cable CBL-SAST-0538 and plastic stand-off FST-SCRW-0074L (2240/2260/2280/22110),2 M.2 PCI-E 3.0 x4 M-Key NVMe via optional add-on card AOC-SLG3-2M2 (2260/2280/22110)
PCI-Exp ^f ess	1 PCI-E 3.0 x16 slot (FH, 10.5" L), 5 PCI-E 3.0 x8 slots (FH, 10.5" L), 1 PCI-E 3.0 x8 slot (LP),1 PCI-E 3.0 x8 slot (internal LP)	Power Supply	
Integrated On-Board		1000W Redundant Power Supplies Titanium Level (96%)	
SATA	SATA3 (6Gbps); RAID 0, 1, 5, 10	Cooling System	
LAN	2 25GbE SFP28 ports,1 RJ45 Dedicated IPMI LAN port	4 Heavy duty 8cm PWM fans	
Add-on Options		Form Factor	
Raid Card	Optional	Form Factor	2U Rackmount
Optical Drive	None	Height	: 3.5" (89 mm),
		Width	: 17.2" (437mm)
		Depth	: 27.76" (705.3mm)
<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit www.tyronesystems.com</p>			

© Intel, the Intel logo,the Intel Inside logo,Xeon,and Intel Xeon Phi are trademarks of Intel Corporation in the U.S and/Or other Countries
 © Specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks .All other brands and names are the property of their respective owners