

# Tyrone Camarero Specifications

# Tyrone

## Camarero DS400U-14R4T

### Key features

- **Virtualization,Cloud Computing,High End Enterprise Server**
- 2nd Generation Intel® Xeon® Scalable Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors., Dual Socket P (LGA 3647) supported, CPU TDP support 205W, 2 UPI up to 10.4 GT/s
- Intel® C621 chipset
- Up to 6TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 6TB 3DS ECC LRDIMM, DDR4-2933MHz, in 24 DIMM slots;Up to 6TB Intel® Optane™ DC Persistent Memory in memory mode.
- 2 PCI-E 3.0 x16 slots (FH, 10.5" L),2 PCI-E 3.0 x8 slots (1 LP, 1 internal LP)
- 4 10GBase-T Ethernet ports
- 4 Hot-swap 3.5" Drive Bays;Optional M.2 NVMe and SATA3 ports
- 8 Heavy duty fans w/ optimal fan speed control
- 750W Redundant Power Supplies, Platinum Level (94%+)



### Processor/Cache

Processor	2nd Generation Intel® Xeon® Scalable Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors., Dual Socket P (LGA 3647) supported, CPU TDP support 205W, 2 UPI up to 10.4 GT/s
-----------	---

### Chipset

Chipset	Intel® C621 Chipset
---------	---------------------

### System Memory

Memory Capacity	Up to 6TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 6TB 3DS ECC LRDIMM, DDR4-2933MHz, in 24 DIMM slots;Up to 6TB Intel® Optane™ DC Persistent Memory in memory mode.
-----------------	---

### Expansion Slots

PCI-Express	2 PCI-E 3.0 x16 (Full-height, 10.5" L), 2 PCI-E 3.0 x8 (1 LP, 1 internal LP)
-------------	--

### Integrated On-Board

SATA	SATA3 (6Gbps); RAID 0, 1, 5, 10
LAN	4 RJ45 10GBase-T Ethernet ports,1 RJ45 Dedicated IPMI LAN port

### Add-on Options

Raid Card	Optional
Optical Drive	None

### Front Panel

LED Indicators	Power LED,Hard drive activity LED,Network activity LEDs,System Overheat LED / Fan fail LED /UID LED
Buttons	Power On/Off button,System Reset button

### Drive Bays

HDD Bays	4 Hot-swap 3.5" drive bays, 4 SATA3 (optional SAS3 via AOC)
M.2	1 M.2 PCI-E 3.0 x4 M-Key NVMe and 1 M.2 M-Key SATA3 via optional riser card RSC-UMR-8, cable CBL-SAST-0538 and plastic stand-off FST-SCRW-0074L (2240/2260/2280/22110),2 M.2 PCI-E 3.0 x4 M-Key NVMe via optional add-on card AOC-SLG3-2M2 (2260/2280/22110)

### Power Supply

750W Redundant Power Supplies, Platinum Level (94%+)

### Cooling System

8 Heavy duty fans with optimal fan speed control

### Form Factor

Form Factor	1U Rackmount
Height	: 1.7" (43mm),
Width	: 17.2" (437mm),
Depth	: 29.7" (754mm)

Email : [info@tyronesystems.com](mailto:info@tyronesystems.com)

For more/current product information, visit  
[www.tyronesystems.com](http://www.tyronesystems.com)