Tyrone Camarero Specifications

Tyrone

Camarero DSA720TN-110RT

Key features

Virtualization, Cloud Computing, All Flash Storage

- Single AMD EPYC™ 7003/7002 Series Processor, (7003 Series Processor drop-in support requires BIOS version 2.0 or newer),Socket SP3, Support CPU TDP up to 280W,Up to 64 Cores
- System on Chip
- 16 DIMM slots, Up to 4TB 3DS ECC DDR4-3200MHz RDIMM/LRDIMM
 Memory Type: DDR4 3200 MHz Registered ECC, 288-pin gold-plated DIMMs
- 2 PCI-E 4.0 x16 (FHHL) slots, 1 PCI-E 4.0 x16 (LP) slot, 2 PCI-E 4.0 x2 NVMe M.2 slots
- Integrated IPMI 2.0 + KVM withdedicated LAN, Software Out of Band License key, (SFT-OOB-LIC) included for OOB BIOS management
- 2x 10GBase-T LAN ports via, Broadcom BCM57416 Controller
- 1 VGA,7 USB 3.0 (4 rear, 2 front, 1 Type A)
- 2 SuperDOM (Disk on Module) ports
- 10 Hot-swap U.2 Gen4/Gen3 NVMe drive support, Optional 10 SATA3 drive support via additional SATA cables
- 6 heavy duty fans with Optimal Fan Speed Control
- 700W/750W Redundant Power Supplies with PMBus, 80 plus Platinum Certified







Processor/Cache

Processor Single AMD EPYC™ 7003/7002 Series Processor,

(7003 Series Processor drop-in support requires BIOS version 2.0 or newer), Socket SP3, Support

CPU TDP up to 280W,Up to 64 Cores

Chipset

Chipset System on Chip

System Memory

Memory Capacity 16 DIMM slots, Up to 4TB 3DS ECC

DDR4-3200MHz RDIMM/LRDIMM

Memory Type: DDR4 3200 MHz Registered

ECC, 288-pin gold-plated DIMMs

Expansion Slots

PCI-Express 2 PCI-E 4.0 x16 (FHHL) slots,

1 PCI-E 4.0 x16 (LP) slot,

2 PCI-E 4.0 x2 NVMe M.2 slots

Integrated Onboard

SATA 2 SATA3 (6 Gbps) ports

LAN 2 RJ45 10GBase-T ports, 1 RJ45 Dedicated

IPMI LAN port

Add-on Options

Raid Card: Optional
Optical Drive: None

Front Panel

Front Panel Power status LED, HDD activity LED, Network

activity LEDs, Universal Information (UID) LED

Buttons Power On/Off button, UID button

Drive Bays

HDD Bays 10 Hot-swap U.2 Gen4/Gen3 NVMe drive

support, Optional 10 SATA3 drive support via

additional SATA cables

Power Supply

700W/750W Redundant Power Supplies with PMBus , 80 plus Platinum Certified.

Cooling System

6 heavy duty fans with Optimal Fan Speed Control

Form Factor

Form Factor 1U Rackmount

Dimensions: Width 17.2" (437mm),

Height 1.7" (43mm), Depth: 23.5" (597mm)

Email: info@tyronesystems.com

For more/current product information, visit

www.tyronesystems.com

AMD the AMD logo inside are trademarks of Advanced Micro Devices in US and / Or other Countries