

Tyrone Camarero Specifications



Camarero IDI100C3R-212

Key features

- 3rd Generation Intel® Xeon® Scalable Processors, 270 W
- Intel® C621A Chipset
- Max 32 DIMM Slots DDR4 (RDIMM), 3DS-RDIMM, Load Reduced DDR4 (LRDIMM), 3DS-LRDIMM ,Intel® Optane™ persistent memory 200 series
- Riser Slot 1:32 Lanes, Riser Slot 2:32 Lanes, Riser Slot 3: 16 Lanes
- 12 HDD/SSD Hot Swap 3.5" drive bays
- 10 SATA Ports, Raid 0/1/5/10
- 8 Integrated SAS Ports
- Three USB 3.0 on the back panel, One USB 3.0 , one USB 2.0 on the front panel, One USB 2.0 internal Type-A
- 2100 W Redundant Power Supply



Processor/Cache	
Processor	3rd Generation Intel® Xeon® Scalable Processors, 270 W
Chipset	
Chipset	Intel® C621A
System Memory	
Memory Capacity	Max 32 DIMM Slots DDR4 (RDIMM), 3DS-RDIMM, Load Reduced DDR4 (LRDIMM), 3DS-LRDIMM ,Intel® Optane™ persistent memory 200 series
Expansion Slots	
PCI-Express	Riser Slot 1:32 Lanes, Riser Slot 2:32 Lanes, Riser Slot 3: 16 Lanes
Integrated Onboard	
SATA	10 SATA Ports, Raid 0/1/5/10
Add-on Options	
Optical Drive:	None
Drive Bays	
HDD Bays	12 HDD/SSD Hot Swap 3.5" drive bays
Power Supply	
	2100 W Redundant Power Supply
Form Factor	
Form Factor	2U Rackmount
Dimensions	712 x 439 x 89 mm
Email : info@tyronesystems.com For more/current product information, visit www.tyronesystems.com	