Tyrone Camarero Specifications

Tyrone

Camarero- SDI10C3R-54

Key Feature

- 3rd Gen Intel® Xeon® Scalable processors,Dual Socket LGA-4189 (Socket P+) supported, CPU TDP supports Up to 185W TDP, 2 UPI up to 11.2 GT/
- Intel® C621A
- Up to 2TB RDIMM, DDR4-3200MHz; Up to 2TB 3DS ECC LRDIMM, DDR4-3200MHz, in 8 DIMM slots
- 4 PCI-E 4.0 x16,M.2 Interface: 2 PCI-E 4.0 x4, M.2 Form Factor: 2280/22110, 2280, M.2 Key: M-Key
- Intel® C621A controller for 12 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- Dual LAN with Intel® i210 Gigabit Ethernet Controller / Dual LAN with Intel® X550 10GBase-T Ethernet Controller
- 1 VGA port
- External: 5.25" x 4, 3.5" x 1; Internal: 3.5" x 5 or 2.5" x5
- Front: 120 x 25 mm x1 PWM Fan,Rear: 120 x 25 mm x1 PWM Fan
- 550/1200W Redundant Power Supply ,Optional : 500/1200W Single Power Supply
- 2U Rackmount Chassis, 12 x 3.5" drive bays

intel inside™ XEON®

Processor/Cache

Processor	3rd Gen Intel® Xeon® Scalable processors Dual Socket LGA-4189 (Socket P+) supported, CPU TDP supports Up to 185W TDP, 2 UPI up to 11.2 GT/s

System Memory

Memory Capacity	Up to 2TB RDIMM, DDR4-3200MHz; Up to 2TB 3DS ECC LRDIMM, DDR4-3200MHz, in 8 DIMM slots

Chipset

Chipset	Intel® C621A

Expansion Slot

Expansion Slot	4 PCI-E 4.0 x16 M.2 Interface: 2 PCI-E 4.0 x4, M.2 Form Factor: 2280/22110, 2280, M.2 Key: M-Key

Integrated Onboard:

SATA	Intel® C621A controller for 12 SATA3 (6 Gbps) ports; RAID 0,1,5,10
Network Controllers	Dual LAN with Intel® i210 Gigabit Ethernet Controller / Dual LAN with Intel® X550 10GBase-T Ethernet Controller

Add-on Options

Raid Card	Optional
Optical Drive	None

Front Panel

Front Panel	Front Control Panel Power Switch, System Reset
Buttons	Power On/Off button

Drive bays

HDD Bays	External: 5.25" x 4, 3.5" x 1; Internal: 3.5" x 5 or 2.5" x5

Power Supply

Power Supply	550/1200W Redundant Power Supply Optional : 500/1200W Single Power Supply

Cooling System

Fans	Front: 120 x 25 mm x1 PWM Fan Rear: 120 x 25 mm x1 PWM Fan

Form Factor

Form Factor	Tower/5U Rackmount

Dimensions

Dimensions	560 x 200 x 430 mm (22" x 7.9" x 16.9"(737mm).(647mm)