

Tyrone Camarero Specifications

Tyrone

Camarero: SDI200C3A-48

Key Feature

- 5th/4th Gen Intel® Xeon® Scalable processors, Dual Socket LGA-4677 (Socket E) , CPU TDP supports up to 350W TDP
- Support CXL
- Intel® C741 Chipset
- Up to 4TB 3DS ECC RDIMM, DDR5-4800MT/s(1DPC) in 16 DIMM slots
- Broadcom BCM57416 Dual ports 10G LAN
- 2 SATA DOM ports
- 2 M.2
- 4 NVMe ports PCIe 5.0 x4 via 2 MCIO connectors
- 5 PCIe 5.0 x16, 1 PCIe 5.0 x8
- 8 SATA 3.0 ports(C741, RAID 0, 1, 5, 10)
- HD Audio 7.1 channel
- 1 USB 3.1 Gen 2, 6 USB 3.0
- 8x 3.5"/2.5" hot-swap SAS drive bay with SES3
- 1200W (1 + 1) Redundant Titanium Level Certified High-Efficiency Power Supply
- Whisper-Quiet (<27dB)



Processor/Cache		Front Panel	
Processor	5th/4th Gen Intel® Xeon® Scalable processors, Dual Socket LGA-4677 (Socket E) , CPU TDP supports up to 350W TDP	LED	Power status LED, HDD activity LED, System Information LED, Power Fail LED, 2 Network Activity LEDs
Chipset	Intel® C741 Chipset	Buttons	On/Off button, System Reset button
System Memory		Ports	2x USB 3.0 Port(s)
Memory Capacity	16 DIMM slots, Up to 4TB 3DS ECC RDIMM, DDR5-4800MHz	Drive bays	
Expansion Slot		HDD Bays	8x 3.5"/2.5" hot-swap SAS drive bay with SES3
PCI-Express	1 PCIe 5.0 x8, 5 PCIe 5.0 x16 , M.2 Interface: 2 PCIe 5.0 x4 ,Form Factor: 2280/22110, Key: M-Key	Power Supply	
Integrated Onboard:		Power Supply	1200W (1 + 1) Redundant Titanium Level Certified High-Efficiency Power Supply
SATA	8 SATA3 ports; RAID 0, 1, 5, 10, 2 SATA3 ports; RAID 0,1	Cooling System	
LAN	Dual LAN with Broadcom BCM57416 10GBase-T		2x 8cm (2800 rpm) PWM Fans & 1x 9cm (2400 rpm) PWM Fans
Add-on Options		Form Factor	
Raid Card	None	Form Factor	4U Rackmount
Optical Drive	None	Dimensions	
		Dimensions	Height -17.8" (452 mm), Width -7" (178 mm), Depth -25.5" (647 mm)
		<p>Email : Info@tyronesystems.com</p> <p>For more/current product information, Visit www.tyronesystems.com</p>	