

Tyrone Camarero Specifications

Tyrone

Camarero- SDI200C3R-28

Key features

- Virtualization, Enterprise Server, Application and data serving, Compute Intensive Applications.
- Dual Socket E (LGA-4677) 5th/4th Gen Intel® Xeon® Scalable processors, supports up to 300W TDP.
- 16 DIMM slots, Up to 4TB DDR5-4800MHz ECC Registered RDIMM.
- 2 PCIe 5.0 x8 LP slot(s), 2 PCIe 5.0 x16 LP slot(s), 2 M.2 PCIe 4.0 x2 NVMe slot(s) (M-key)
- Dual ports 1G LAN/Dual ports 10G LAN
- 8 x 3.5" hot-swap SAS3/SATA drive bay.
- 3 middle 8cm Fan(s).
- 600W/650W/800W/1200W Redundant Power supply.



Processor/Cache	
Processor	Dual Socket E (LGA-4677) 5th/4th Gen Intel® Xeon® Scalable processors Note: supports up to 300W TDP CPUs (Aircooled) CPUs with high TDP (air cooled) only supported under specific conditions.
Chipset	
Chipset	Intel® C741 Chipset
System Memory	
Memory Capacity	Memory Capacity: 16 DIMM slots ,Up to 4TB: 16x 256 GB DRAM, Memory Type: 4800MHz ECC DDR5 RDIMM
Expansion Slots	
PCI-Express	2 PCIe 5.0 x8 LP slot(s), 2 PCIe 5.0 x16 LP slot(s), 2 M.2 PCIe 4.0 x2 NVMe slot(s) (M-key)
Integrated On-Board	
SATA	SATA3 (6Gbps)
Network Connectivity	Dual ports 1G LAN/Dual ports 10G LAN
Add-on Options	
Raid card	Optional
Optical Drive	Optional

Front Panel	
LED	HDD activity, Network activity, Power status, System information (overheat/UID)
Buttons	Power On/Off button, System Reset button
Drive bays	
Drive bays	8 x 3.5" hot-swap SAS3/SATA drive bay.
Peripheral bays	1x slim DVD drive bays (optional)
Power Supply	
Power Supply	600W/650W/800W/1200W Redundant Power supply
Cooling System	
Fans	3 middle 8cm Fan(s)
Form Factor	
Form Factor	2U Rackmount
Dimensions	
Dimensions	Height - 3.5" (89mm), Width 17.2" (437mm) Depth 25.5" (647mm).
<p>Email : Info@tyronesystems.com</p> <p>For more/current product information, Visit www.tyronesystems.com</p>	