

# Tyrone Camarero Specifications

# Tyrone

## Camarero SS0iTR-45TR

### Key features

- 10th Generation Intel® Core™ i9/Core™ i7/Core™ i5/Core™ i3/Pentium®/Celeron® Processor Single Socket LGA-1200 (Socket H5) supported, CPU TDP support Up to 140W TDP
- Intel® Z490
- Up to 128GB Unbuffered non-ECC UDIMM, DDR4-2933MHz, in 4 DIMM slots  
2933 MHz to 4000+MHz(OC) in four 288-pin memory slots.
- 4 PCI-E 3.0 x16 slots (16/NA/16/NA or 8/8/8/8), 1 PCI-E 3.0 x1  
M.2 : M.2 Interface: 2 PCI-E 3.0 x4, RAID 0 & 1 and 1 CNVi, RAID 0 & 1, Form Factor: 2260/2280/22110  
Key: M-Key , E-Key, RSTe software raid; M.2-E1 port pre-installed one Intel Wi-Fi 6(802.11ax)+BT5.1 module  
2 M.2 M-Key PCI-E 3.0 x4, 2260/2280/22110
- 1 DP (DisplayPort) port, 1 HDMI port, DP version 1.4, HDMI version 2.0a
- Single LAN with Intel® single Ethernet PHY i219V, Single LAN with Aquantia® AQC107 10G Ethernet Controller
- External: 5.25" x 4, 3.5" x 1; Internal: 3.5" x 5 or 2.5" x 5
- Front:120 x 25 mm x1 PWM Fan, Rear: 120 x 25 mm x1 PWM Fan
- 550/1200 Redundant Power supply, 80 Plus Platinum



Processor/Cache	
Processor	10th Generation Intel® Core™ i9/Core™ i7/Core™ i5/Core™ i3/Pentium®/Celeron® Processor Single Socket LGA-1200 (Socket H5) supported, CPU TDP support Up to 140W TDP
Chipset	
Chipset	Intel® Z490
System Memory	
Memory Capacity	Up to 128GB Unbuffered non-ECC UDIMM, DDR4-2933MHz, in 4 DIMM slots 2933 MHz to 4000+MHz(OC) in four 288-pin memory slots.
Expansion Slots	
PCI-Express	4 PCI-E 3.0 x16 slots (16/NA/16/NA or 8/8/8/8), 1 PCI-E 3.0 x1 M.2 : M.2 Interface: 2 PCI-E 3.0 x4, RAID 0 & 1 and 1 CNVi, RAID 0 & 1, Form Factor: 2260/2280/22110 Key: M-Key , E-Key, RSTe software raid; M.2-E1 port pre-installed one Intel Wi-Fi 6(802.11ax)+BT5.1 module 2 M.2 M-Key PCI-E 3.0 x4, 2260/2280/22110
Integrated Onboard	
SATA	4 SATA3 (6Gbps) ports
LAN	1 RJ45 Gigabit Ethernet LAN ports, 1 RJ45 10GBase-T ports
Add-on Options	
Raid Card	Optional
Optical Drive	None

Front Panel	
Front Panel	Front Control Panel Power Switch, System Reset, USB 3.0 x 2
Buttons	Power On/Off button
Drive Bays	
HDD Bays	External: 5.25" x 4, 3.5" x 1; Internal: 3.5" x 5 or 2.5" x 5
Power Supply	
	550/1200 Redundant Power supply, 80 Plus Platinum
Cooling System	
	Front:120 x 25 mm x1 PWM Fan, Rear: 120 x 25 mm x1 PWM Fan
Form Factor	
Form Factor	5U Rackmount
Dimensions:	560 x 200 x 430 mm (22" x 7.9" x 16.9")
<p><b>Email : <a href="mailto:info@tyronesystems.com">info@tyronesystems.com</a></b></p> <p><b>For more/current product information, visit</b></p> <p><b><a href="http://www.tyronesystems.com">www.tyronesystems.com</a></b></p>	

Intel, the Intel logo, the Intel Inside logo, Xeon, and Intel Xeon Phi are trademarks of Intel Corporation in the U.S and/or Other Countries.  
Specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks. All other brands and names are the property of their respective owners.