

Tyrone Camarero Specifications

Camarero SS400TR-11

Key features

Mainstream, Entry Appliance, Low Power, Cost effective

- Single socket H4 (LGA 1151) supports Intel® Xeon® processor E3-1200 v6/v5, Intel® 7th/6th Gen. Core™ i3 series, Intel® Celeron® and Intel® Pentium®
- Intel® C232 chipset
- 1x 3.5" Fixed drive bay or 2x 2.5" drive option
- Up to 64GB Unbuffered ECC UDIMM DDR4 2400MHz; 4 DIMM slots
- 1x PCI-E 3.0 x8 AOC slot
- 2x GbE ports with Intel® i210-AT 1x shared IPMI port
- I/O ports: 1x VGA, 1x COM, 2x USB 2.0, USB 3.0
- 200W Multi-output power supply



Processor/Cache

Processor	Single socket H4 (LGA 1151) supports Intel® Xeon® processor E3-1200 v6/v5, Intel® 7th/6th Gen. Core™ i3 series, Intel® Celeron® and Intel® Pentium®
-----------	---

Chipset

Chipset	Intel® C232 chipset
---------	---------------------

System Memory

Memory Capacity	Up to 64GB Unbuffered ECC UDIMM DDR4 2400MHz; 4 DIMM slots
-----------------	--

Expansion Slots

PCI Express	1x PCI-E 3.0 x8 AOC slot
-------------	--------------------------

Integrated On-Board

SATA	SATA3 (6Gbps) via C232 controller RAID 0, 1, 5, 10 support
LAN	2x RJ45 Gigabit Ethernet LAN ports, 1x RJ45 Shared IPMI LAN port

Add-on Options

Raid	Optional
Optical Drive	None

Front Panel

LED	Power LED, Hard drive activity LED, 2x Network activity LEDs, System Overheat LED, Information LED (temp., status)
Buttons	Power On/Off button, System Reset button

Drive Bays

HDD Bays	1x 3.5" or 2x 2.5" internal drive bays, 2x 2.5" Fixed drives internal
----------	---

Power Supply

200W Multi-output power supply

Cooling System

2x 40x28mm 4-pin PWM Cooling Fans, 1x FAN-0147L4 option for 80W CPU

Form Factor

"Enterprise Grade" Ultra Compact Form Factor (ii)

Email : info@tyronesystems.com

For more/current product information, visit

www.tyronesystems.com