

# Tyrone Camarero Specifications



## Camarero SS400TR-14L

### Key features

#### Web Hosting, VM ,Compact Network Appliance

- Single Socket P (LGA 3647), 2nd Gen Intel® Xeon® Scalable Processors and Intel® Xeon® Scalable Processors, Support CPU TDP 70-165W
- Intel® C621 chipset
- 6 DIMMs; up to 1.5TB 3DS ECC, DDR4-2933MHz RDIMM/LRDIMM
- 1 PCI-E 3.0 x16 slot (FH, HL)
- 4 Hot-swap 3.5" SATA3 bays w/ RAID
- 2x 1GbE with Marvell® 88E1512
- Integrated IPMI 2.0 and KVM with Dedicated LAN
- 1 VGA, 1 COM, 2 USB 3.0, 2 USB 2.0
- 350W High-efficiency Power Supply Platinum Level Certified



Processor/Cache	
Processor	Single Socket P (LGA 3647), 2nd Gen Intel® Xeon® Scalable Processors and Intel® Xeon® Scalable Processors, Support CPU TDP 70-165W
Chipset	
Chipset	Intel® C621 Chipset
System Memory	
Memory Capacity	6 DIMMs; up to 1.5TB 3DS ECC, DDR4-2933MHz RDIMM/LRDIMM
Expansion Slots	
PCI-Express	1 PCI-E 3.0 x16 slot (FH, HL), M.2 : 1x M.2 Interface: PCI-E 3.0 x4 Form Factor: 2242, 2280, Key: M-Key, Double Height Connector
Integrated Onboard	
SATA	SATA3 (6Gbps) via C621 controller RAID 0, 1, 5, 10 support
LAN	2 RJ45 1GbE LAN ports, 1 RJ45 Dedicated IPMI LAN port
Add-on Options	
Raid Card	Optional
Optical Drive	Optional

Drive Bays	
HDD Bays	4 Hot-swap 3.5" SATA3 drive bays
Peripheral Bays	Optional slim optical device bay, optional FDD/USB bay
Power Supply	
	350W High-efficiency Power Supply Platinum Level Certified
Cooling System	
	4x 40x28mm PWM fans, Optional 2 fans for AOC cooling
Form Factor	
Form Factor	1U Rackmount
Dimensions	Height : 1.7" (43mm), Width :17.2" (437mm), Depth : 19.85" (503mm)
<p><b>Email : <a href="mailto:info@tyronesystems.com">info@tyronesystems.com</a></b></p> <p><b>For more/current product information, visit</b></p> <p><b><a href="http://www.tyronesystems.com">www.tyronesystems.com</a></b></p>	