

Tyrone Camarero Specifications

Tyrone

Camarero SS400TR-14R-1585L

Key features

- **Support VHD & Quick Sync Video Iris Pro Optimizations GT4e Build-in**
- Intel® Xeon® processor E3-1585L v5, Single socket FCBGA 1440, 4-Core, 8 Threads, 45W
- Intel® C236 chipset
- Up to 64GB ECC Unbuffered SO-DIMM, DDR4-2133MHz; 4 DIMM slots
- 4x 3.5" Hot-swap SATA3 bays w/ RAID
- 1 PCI-E 3.0 x8 (in x16) AOC slot, M.2 Interface: PCIe 3.0 x4 and SATA, M.2 Form Factor: 2242, 2280, 22110
- 2x 1GbE ports with Intel® i350
- Integrated IPMI 2.0 and KVM with Dedicated LAN
- I/O ports: 1 VGA, 1 COM, 2 USB 3.0 (front/rear), USB 2.0
- 4x 40x28mm 4-pin PWM Cooling Fans
- 400W Redundant Platinum Power Supplies w/ BBP® option



Processor/Cache	
Processor	Intel® Xeon® processor E3-1585L v5, Single socket FCBGA 1440, 4-Core, 8 Threads, 45W
Chipset	
Chipset	Intel® C236 chipset
System Memory	
Memory Capacity	Up to 64GB ECC Unbuffered SO-DIMM, DDR4-2133MHz; 4 DIMM slots
Expansion Slots	
PCI-Express	1 PCI-E 3.0 x8 (in x16) AOC slot, M.2 Interface: PCIe 3.0 x4 and SATA, M.2 Form Factor: 2242, 2280, 22110
Integrated On-Board	
SATA	SATA3 (6Gbps) via C236 controller RAID 0, 1, 5, 10 support
LAN	2 RJ45 Gigabit Ethernet LAN ports, 1 RJ45 Dedicated IPMI LAN port
Add-on Options	
Raid Card	Optional
Optical Drive	Optional
Front Panel	
LED	Power LED, Hard drive activity LED, 2 Network activity LEDs, System Information LED
Buttons	Power On/Off button, System Reset button
Drive Bays	
Drive bays	4x 3.5" Hot-swap SATA3 bays w/ RAID
Peripheral Drives	Optional 2.5" drive adapter, Optional slim DVD drive
Power Supply	
	400W Redundant Platinum Power Supplies w/ BBP® option
Cooling System	
	4x 40x28mm 4-pin PWM Cooling Fans
Form Factor	
Form Factor	1U Rackmount
Height:	1.7" (43mm),
Width:	17.2" (437mm),
Depth:	19.8" (503mm)
Email : info@tyronesystems.com	
For more/current product information, visit www.tyronesystems.com	