

Tyrone Camarero Specifications

Camarero SS400TR-14RT

Tyrone

Key features

- **Web Hosting, VM, Application and Data Serving, Database Applications**
- 2nd Generation Intel® Xeon® Scalable Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors., Single Socket P (LGA 3647) supported, CPU TDP support 205W
- Intel® C622 chipset
- Up to 2TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 2TB 3DS ECC LRDIMM, DDR4-2933MHz, in 8 DIMM slots
- 4 Hot-swap 3.5" SATA3 bays w/ RAID
- 1 PCI-E 3.0 x16 slot
- 2x 10GBase-T ports with Intel X772 + X557
- Integrated IPMI 2.0 and KVM with Dedicated LAN
- 1 VGA, 2 COM, 4 USB 3.0, 2 USB 2.0
- 400W Redundant Platinum Power Supplies w/ BBP® option



Processor/Cache

Processor	2nd Generation Intel® Xeon® Scalable Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors., Single Socket P (LGA 3647) supported, CPU TDP support 205W
-----------	--

Chipset

Chipset	Intel® C622 chipset
---------	---------------------

System Memory

Memory Capacity	Up to 2TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 2TB 3DS ECC LRDIMM, DDR4-2933MHz, in 8 DIMM slots
-----------------	--

Expansion Slots

PCI Express	1 PCI-E 3.0 x16 slot
-------------	----------------------

Integrated On-Board

SATA	SATA3 (6Gbps) via C622 controller, RAID 0, 1, 5, 10 support
LAN	2 RJ45 10GBase-T LAN ports, 1 RJ45 Dedicated IPMI LAN port

Add-on Options

Raid Card	Optional
Optical Drive	Optional

Front Panel

LED	Power LED, Hard drive activity LED, Network activity LEDs, System Overheat LED
Buttons	Power On/Off button, System Reset button

Drive Bays

HDD Bays	4 Hot-swap 3.5" SATA3 drive bays, M.2 mini-PCI-e support
Peripheral Bays	Optional slim optical device bay, optional FDD/USB bay

Power Supply

400W Redundant Platinum Power Supplies w/ BBP® option

Cooling System

4x 40mm mid-fans

Form Factor

Form Factor	1U Rackmount
Width:	17.2" (437mm),
Height:	1.7" (43mm),
Depth:	19.8" (503mm)

Email : info@tyronesystems.com

For more/current product information, visit
www.tyronesystems.com