

Tyrone Camarero Specifications

Tyrone®

Camarero SS400TR-14TL

Key features

Web Hosting, VM , Application and Data Serving, Database Applications

- Single socket P (LGA 3647) supports Intel® Xeon® Scalable Processors
- Intel® C622 chipset
- 4 Hot-swap 3.5" SATA3 bays w/ RAID
- 8 DIMMs; up to 2TB 3DS ECC DDR4-2933MHzRDIMM/LRDIMM
- 1 PCI-E 3.0 x16 slot
- 2x 10GBase-T ports with Intel X772 + X557
- Integrated IPMI 2.0 and KVM with Dedicated LAN
- 1 VGA, 2 COM, 4 USB 3.0, 2 USB 2.0
- 4x 40mm mid-fans
- 350W High-efficiency Power Supply Platinum Level Certified



Processor/Cache	
Processor	Single socket P (LGA 3647) supports Intel® Xeon® Scalable Processors
Chipset	
Chipset	Intel® C622 chipset
System Memory	
Memory Capacity	8 DIMMs; up to 2TB 3DS ECC DDR4-2933MHzRDIMM/LRDIMM
Expansion Slots	
PCI-Express	1 PCI-E 3.0 x16 slot
Integrated On-Board	
SATA	SATA3 (6Gbps) via C622 controller RAID 0, 1, 5, 10 support
LAN	2 RJ45 10GBase-T LAN ports, 1 RJ45 Dedicated IPMI LAN port
Add-on Options	
Raid Card	Optional
Optical Drive	Optional

Front Panel	
LED Indicators	Power LED, Hard drive activity LED, Network activity LEDs, System Overheat LED
Buttons	Power On/Off button, System Reset Button
Drive Bays	
HDD Bays	4 Hot-swap 3.5" SATA3 drive bays
M.2	M.2 mini-PCI-e support
Peripheral Drives	Optional slim optical device bay, optional FDD/USB bay
Power Supply	
350W High-Efficiency Supply Platinum Level Certified	
Cooling System	
4x 40mm mid-fans	
Form Factor	
Form Factor	1U Rackmount
Height	: 1.7" (43mm)
Width	: 17.2" (437mm)
Depth	: 19.8" (503mm)
Email : info@tyronesystems.com	
For more/current product information, visit www.tyronesystems.com	