

Tyrone Camarero Specifications

Tyrone

Camarero SS400TR-55T

Key features

High Performance, VROC support

- 2nd Gen Intel® Xeon® Scalable Processors and Intel® Xeon® Scalable Processors, , Single Socket LGA-3647 (Socket P) supported, CPU TDP support Up to 205W TDP
- Intel® C622
- Up to 2TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 2TB 3DS ECC LRDIMM, DDR4-2933MHz, in 8 DIMM slots
- 1 PCI-E 3.0 x16, 1 PCI-E 3.0 x16 (x16 || x8), 1 PCI-E 3.0 x8 (x0 || x8), 1 PCI-E 3.0 x8, 1 PCI-E 3.0 x4 (in x8)
- 2 10GbE LAN ports
- 10 SATA3 (6Gbps) via C622
- I/O: 1 VGA, 2 COM, TPM header
- 5 USB 3.0 (2 rear, 1 Type-A, 2 via header), 6 USB 2.0 (2 rear, 4 via headers)
- M.2 NGFF connector, M.2 Interface: PCI-E 3.0 x4 and SATA, Form Factor: 2280, 22110, Key: M-Key, Double Height Connector
- External: 5.25" x 4, 3.5" x 1; Internal: 3.5" x 5 or 2.5" x5
- Front: 120 x 25 mm x1 PWM Fan, Rear: 120 x 25 mm x1 PWM Fan
- 550/1200W Redundant Power Supply, 80Plus Platinum
Optional :500/1200W Single Power Supply, 80Plus Platinum



Processor/Cache		Front Panel	
Processor	2nd Gen Intel® Xeon® Scalable Processors and Intel® Xeon® Scalable Processors, , Single Socket LGA-3647 (Socket P) supported, CPU TDP support Up to 205W TDP	LEDs	2 Network Activity LEDs, HDD Fail LED, Power Status LED, Power Fail LED, System Information LED
Buttons		Buttons	Power On/Off button, System Reset Button
Chipset		Drive Bays	
Chipset	Intel® C622	HDD Bays	External: 5.25" x 4, 3.5" x 1; Internal: 3.5" x 5 or 2.5" x5
System Memory		Power Supply	
Memory Capacity	Up to 2TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 2TB 3DS ECC LRDIMM, DDR4-2933MHz, in 8 DIMM slots	550/1200W Redundant Power Supply, 80Plus Platinum Optional :500/1200W Single Power Supply, 80Plus Platinum	
Expansion Slots		Cooling System	
PCI-Express	1 PCI-E 3.0 x16, 1 PCI-E 3.0 x16 (x16 x8), 1 PCI-E 3.0 x8 (x0 x8), 1 PCI-E 3.0 x8, 1 PCI-E 3.0 x4 (in x8)	Front: 120 x 25 mm x1 PWM Fan, Rear: 120 x 25 mm x1 PWM Fan	
Integrated Onboard		Form Factor	
SATA	Intel® C622 controller for 10 SATA3 (6 Gbps) ports; RAID 0,1,5,10 Intel® C621 controller for 12 SATA3 (6 Gbps) ports; RAID 0,1,5,10	Form Factor	Tower/Convertible/5U Rackmount
LAN	2 RJ45 10GBase-T ports	Dimensions:	560 x 200 x 430 mm (22" x 7.9" x 16.9")
Add-on Options		<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit</p> <p>www.tyronesystems.com</p>	
Raid Card	Optional		
Optical Drive	None		