

Tyrone Camarero Specifications

Camarero SS400TW-14T

Key features

- **DB Processing & Storage, Data Center Applications, Firewall Applications**
- 2nd Generation Intel® Xeon® Scalable Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors., Single Socket P (LGA 3647) supported, CPU TDP support 205W
- Intel® C622 chipset
- Up to 1.5TB 3DS ECC RDIMM, DDR4-2933MHz;
Up to 1.5TB 3DS ECC LRDIMM, DDR4-2933MHz, in 6 DIMM slots
- 2 PCI-E 3.0 x16 (FHFL) slots, 1 PCI-E 3.0 x8 (LP) slot
- 4 Hot-swap 3.5" SATA3 drive bays, 1 slim DVD-ROM drive bay
- 2x 10GBase-T ports with Intel X772 + X557
- 1 VGA, 2 COM, 2 USB 3.0, 2 USB 2.0
- 2 SuperDOM (Disk on Module) ports
- 600W Multi Output Power Supply, Platinum Level High-efficiency



Processor/Cache

Processor	2nd Generation Intel® Xeon® Scalable Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors., Single Socket P (LGA 3647) supported, CPU TDP support 205W
-----------	--

Chipset

Chipset	Intel® C622 chipset
---------	---------------------

System Memory

Memory Capacity	Up to 1.5TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 1.5TB 3DS ECC LRDIMM, DDR4-2933MHz, in 6 DIMM slots
-----------------	---

Expansion Slots

PCI Express	2 PCI-E 3.0 x16 (FHFL) slots, 1 PCI-E 3.0 x8 (LP) slot
-------------	---

Integrated On-Board

SATA	SATA3 (6Gbps); RAID 0, 1, 5, 10
LAN	2 RJ45 10GBase-T LAN ports, 1 RJ45 dedicated IPMI LAN port

Add-on Options

Raid	Optional
Optical Drive	Optional

Front Panel

LED	Power LED, Hard drive activity LED, Network activity LEDs, System Overheat LED, Information LED
-----	---

Buttons	Power On/Off button, System Reset button
---------	--

Drive Bays

HDD Bays	4 Hot-swap 3.5" SATA3 drive bays. M.2 mini-PCI-e support
----------	---

Peripheral Drives	1 Slim DVD-ROM drive bay
-------------------	--------------------------

Power Supply

600W Multi Output Power Supply, Platinum Level High-efficiency

Cooling System

5 Counter-rotation 40x56mm PWM fans, 1 fan for AOC cooling (option)
--

Form Factor

Form Factor	1U Rackmount
Width	17.2" (437mm)
Height	1.7" (43mm)
Depth	25.6" (650mm)

Email : info@tyronesystems.com

For more/current product information, visit

www.tyronesystems.com