

# Tyrone Camarero Specifications

# Tyrone

## Camarero SS400Ti-54L

### Key features

- 8th/9th Generation Intel® Core™ i9/Core™ i7/Core™ i5/Core™ i3/Pentium®/Celeron® Processor, Intel® Xeon® E-2100/ E-2200 Processor, Single Socket LGA-1151 (Socket H4) supported, CPU TDP supports Up to 95W TDP
- Intel® C246
- Up to 128GB Unbuffered ECC/non-ECC UDIMM, DDR4-2666MHz, in 4 DIMM slots
- 1 PCI-E 3.0 x4, 1 PCI-E 3.0 x1, 2 PCI-Ex16 slots are running at NA/16, or 8/81 - 5V PCI 32bit, M.2 Interface: 2 PCI-E 3.0 x4M.2 Form Factor: 2242/2260/2280/22110, M.2 Key: M-Key, M.2#1~2 are shared with PCI-Ex4 slot, M.2#2 is shared with U.2U.2 Interface: 1 PCI-E 3.0 x4
- 1 HDMI port, 1 DVI - D port, 1 DP (DisplayPort) port, 1 VGA port, Intel UHD P630 graphic (For CPU Xeon E-21XXG series only)
- Intel® C246 controller for 8 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- Single LAN with Intel® Ethernet Controller I210-AT, Shared with IPMI, Single LAN with Intel® PHY I219LM LAN controller
- External: 5.25" x 4, 3.5" x 1, Internal: 3.5" or 2.5" x 5
- 500/1200 Single Power Supply, 80 Plus Platinum
- Front: 120 x 25 mm x1 PWM Fan, Rear: 120 x 25 mm x1 PWM Fan



### Processor/Cache

**Processor** 8th/9th Generation Intel® Core™ i9/Core™ i7/Core™ i5/Core™ i3/Pentium®/Celeron® Processor, Intel® Xeon® E-2100/ E-2200 Processor, Single Socket LGA-1151 (Socket H4) supported, CPU TDP supports Up to 95W TDP

### Chipset

**Chipset** Intel® C246

### System Memory

**Memory Capacity** Up to 128GB Unbuffered ECC/non-ECC UDIMM, DDR4-2666MHz, in 4 DIMM slots

### Expansion Slots

**PCI-Express** 1 PCI-E 3.0 x4, 1 PCI-E 3.0 x1, 2 PCI-Ex16 slots are running at NA/16, or 8/8, 1 - 5V PCI 32bit

### Integrated On-Board

**SATA** Intel® C246 controller for 8 SATA3 (6 Gbps) ports; RAID 0,1,5,10  
**LAN** Single LAN with Intel® Ethernet Controller I210-AT, Shared with IPMI, Single LAN with Intel® PHY I219LM LAN controller

### Add-on Options

**Raid Card** Optional  
**Optical Drive** Optional

### Front Panel

**Front Panel** Front Control Panel Power Switch, System Reset  
**Buttons** Power On/Off button

### Drive Bays

**Drive Bays** External: 5.25" x 4, 3.5" x 1, Internal: 3.5" or 2.5" x 5  
**Peripheral Drives** Optional

### Power Supply

500/1200W Single PS, 80 Plus platinum

### Cooling System

Front: 120 x 25 mm x1 PWM Fan, Rear: 120 x 25 mm x1 PWM Fan

### Form Factor

**Form Factor** Tower/Convertible/SU Rackmount  
**Dimensions** 560 x 200 x 430 mm (22" x 7.9" x 16.9")

Email : [info@tyronesystems.com](mailto:info@tyronesystems.com)

For more/current product information, visit [www.tyronesystems.com](http://www.tyronesystems.com)