Tyrone Camarero Specifications

Camarero SS40CTR-14L

Key features

- 8th/9th Generation Intel® Core™i3/Pentium®/Celeron® Processor, Intel® Xeon® E-2100/E-2200
 Processor, Single Socket LGA-1151 (Socket H4) supported, CPU TDP supports Up to 95W TDP
- Intel® C242 chipset
- . Up to 128GB DDR4 2666MHz ECC UDIMM; 4 DIMM slots
- 1 PCI-E 3.0 x8 (in x16 slot),2 PCI-E 3.0 x4 (in x8 slot),
 M.2 Interface: 1 PCI-E 3.0 x4 Form Factor: 2280/22110,
 Key: M-Key Double Height Connector
- . Dual GbE LAN with Intel® i210-AT
- 6 SATA3 (6Gbps) ports;RAID 0, 1, 5, 10
- M.2 NGFF connector
- . I/O: 1 VGA, 2 COM, 2 SuperDOM, and TPM header
- 4 x 3.5" hot-swap SAS/SATA
- 4 x 40x28mm PWM fan(s), Optional 2 x 40x28mm PWM fan(s)
- 350W Multi-output power supply / 400W Redundant Power Supply.









Processor/Cache

8th/9th Generation Intel® Core™i3/
Processor Pentium®/Celeron® Processor Intel®

Pentium®/Celeron® Processor, Intel® Xeon® E-2100/E-2200 Processor, Single Socket LGA-1151 (Socket H4) supported, CPU TDP supports Up to

95W TDP

Chipset

Chipset Intel® C242 chipset

System Memory

Memory Capacity Up to 128GB DDR4 2666MHz ECC

UDIMM; 4 DIMM slots

Expansion Slots

PCI-Express 1 PCI-E 3.0 x8 (in x16 slot),

2 PCI-E 3.0 x4 (in x8 slot), M.2 Interface: 1 PCI-E 3.0 x4 Form Factor: 2280/22110,

Key: M-Key Double Height Connector

Integrated On-Board

SATA Intel® C242 controller for 6 SATA3

(6 Gbps) ports; RAID 0,1,5,10

Add-on Options

Raid Card Optional

Optical Drive Optional

Front Panel

LED 2 Network Activity LEDs,HDD activity LED,

Power Status LED, System Information LED

Buttons Power On/Off button, System Reset Button

Drive Bays

HDD Drives 4 x 3.5" hot-swap SAS/SATA

Peripheral Drives Optional 1 x Slim DVD-ROM Drive

Power Supply

350W Multi-output power supply / 400W Redundant Power Supply .

Cooling System

4 x 40x28mm PWM fan(s), Optional 2 x 40x28mm PWM fan(s)

Form Factor

Form Factor 1U Rackmount

Email: info@tyronesystems.com

For more/current product information, visit

www.tyronesystems.com

o Intel, the Intel logo, the Intel Inside logo, Xeon, and Intel Xeon Phi are trademarks of Intel Corporation in the U.S and/Or other Countries

O Specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks. All other brands and names are the property of their respective owners