

Tyrone Camarero Specifications

Camarero SS4C0TA-26L

Key features

- Intel® 8th/9th Generation Core i9/Core i7/Core i5/Core i3/Pentium®/Celeron® series Processor, Intel® Xeon® E-2100 Processor, Intel® Xeon® E-2200 Processor. Single Socket LGA-1151 (Socket H4) supported, CPU TDP support Up to 95W TDP
- Intel® C246
- Up to 128GB Unbuffered ECC/non-ECC UDIMM, DDR4-2666MHz, in 4 DIMM slots
- 1 PCI-E 3.0 x4, 1 PCI-E 3.0 x1, 2 PCI-Ex16 slots are running at NA/16, or 8/8, 1 - 5V PCI 32bit, M.2 Interface: 2 PCI-E 3.0 x4, Form Factor: 2242/2260/2280/22110, Key: M-Key, M.2#1~2 are shared with PCI-Ex4 slot, M.2#2 is shared with U.2
- 1 HDMI port, 1 DVI - D port, 1 DP (DisplayPort) port, 1 VGA port, Intel UHD P630 graphic (For CPU Xeon E-21XXG series only)
- Intel® C246 controller for 8 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- Single LAN with Intel® Ethernet Controller I210-AT, Single LAN with Intel® PHY I219LM LAN controller
- 6 x 3.5" hot-swap drive bay
- 4 x 8cm (7000 RPM) hot-swap PWM cooling fan(s)
- 600/650W Multi output power supply 24pin output

Tyrone®



Processor/Cache

Processor	Intel® 8th/9th Generation Core i9/ Core i7/Core i5/Core i3/Pentium®/ Celeron® series Processor, Intel® Xeon® E-2100 Processor, Intel® Xeon® E-2200 Processor. Single Socket LGA-1151 (Socket H4) supported, CPU TDP support Up to 95W TDP
-----------	---

Chipset

Chipset	Intel® C246
---------	-------------

System Memory

Memory Capacity	Up to 128GB Unbuffered ECC/non-ECC UDIMM, DDR4-2666MHz, in 4 DIMM slots
-----------------	---

Expansion Slots

PCI-Express	1 PCI-E 3.0 x4, 1 PCI-E 3.0 x1, 2 PCI-Ex16 slots are running at NA/16, or 8/8, 1 - 5V PCI 32bit, M.2 Interface: 2 PCI-E 3.0 x4, Form Factor: 2242/2260/2280/22110, Key: M-Key, M.2#1~2 are shared with PCI-Ex4 slot, M.2#2 is shared with U.2
-------------	---

Integrated On-Board

SATA	Intel® C246 controller for 8 SATA3 (6 Gbps) ports; RAID 0,1,5,10
LAN	2 1GbE LAN ports

Add-on Options

Raid Card	Optional
Optical Drive	Optional

Front Panel

LED	2 Network Activity LEDs, Fan Fail/System Over Heat LED, HDD activity LED, Power Status LED
Buttons	Power On/Off button, System Reset Button

Drive Bays

HDD Drives	6 x 3.5" hot-swap drive bay
Peripheral Drives	1 x slim DVD-ROM drive bay

Power Supply

600/650W Multi output power supply 24pin output

Cooling System

4 x 8cm (7000 RPM) hot-swap PWM cooling fan(s)

Form Factor

Form Factor	2U Rackmount
Height:	3.5" (89 mm),
Width:	16.8" (426 mm),
Depth:	25.6" (650 mm)

Email : info@tyronesystems.com

For more/current product information, visit

www.tyronesystems.com